Electrical Plug Connector - Page 1 of 2

AeroBase Group

View Online at https://aerobasegroup.com/nsn/5935-01-161-1983

Threa	d Class:
2a	
Threa	d Direction:
Right-ł	hand
Body	Style:
Straigh	nt shape, internal coupling w/strain relief
Body	Length:
2.281 i	inches
Overa	II Diameter:
0.719 i	inches
Envirc	onmental Protection:
Moistu	ire proof and salt water resistant and vibration proof and shock resistant and cold resistant and heat resistant and explosion proof
Cable	Entrance Diameter:
Betwe	en 0.468 inches and 0.922 inches
Threa	ded Device Type:
Coupli	ng facility
Mating	g End Quantity:
1	
Conta	ct Position Arrangement Style:
24-7 si	ingle mating end
Conta	ct Removability:
Remov	vable single mating end all contact groupings
Conta	ct Maximum Current Rating In Amps:
41.0 si	ingle mating end 1st contact grouping
Conta	ct Maximum Ac Voltage Rating In Volts:
500.0	single mating end all contact groupings
Conta	ct Maximum Dc Voltage Rating In Volts:
700.0	single mating end all contact groupings
Polari	zation Method:
Keywa	ay or multiple keyway
Insert	Position In Deg:
250.0	
Shell 1	Туре:
Solid	
Conne	ector Locking Method:
Interna	ally threaded coupling nut
Conne	ector Cable Strain Relief Method:
Cable	clamp
Threa	d Size:
1.375	inches
Termi	nal Location:
Back s	single mating end all contact groupings

NSN 5935-01-161-1983 Electrical Plug Connector - Page 2 of 2



Conner allov sir	ngle mating end all contact groupings
Contact Surfac	
	ting end all contact groupings
Insert Material:	
	c single mating end
-	e Treatment Specification:
	al specification single treatment response single mating end all contact groupings
Terminal Type:	
	le mating end all contact groupings
Shell Material:	
Aluminum alloy	
Shell Surface T	reatment:
Chromate	
Included Conta	act Quantity:
2 single mating	end 1st contact grouping
Included Conta	act Type:
Round socket s	ingle mating end all contact groupings
Precious Mater	rial And Location:
Contact surface	s silver
Precious Mater	rial And Weight:
0.024 silver grai	ns, troy
Precious Mater	ial:
Silver	
Thread Series	Designator:
Unef	
Shelf Life:	
N/a	
Unit Of Measur	e:
Demilitarizatio	n:
No	
Fiig:	