## NSN 5935-01-161-2946

Telephone Jack - Page 1 of 2





**Electrical Insulation Feature:** 

Insulated from panel

#### **Body Style:**

Dual hole or slot mounted

## **Overall Length:**

4.031 inches

## Mounting Hole Diameter:

0.156 inches

#### Mounting Bushing Length:

0.562 inches

#### Body Width:

0.562 inches

#### **Distance Between Mounting Facility Centers:**

1.375 inches

#### **Bushing Accommodation Hole Shape:**

Double round plain

#### Accommodated Finger Type:

Three conductor, slender spherical tip all fingers

#### Finger Accommodation Diameter:

0.250 inches all fingers

## Finger Accommodation Length:

1.188 inches all fingers

## Center To Center Distance Between Finger Accommodations:

0.625 inches

#### **Mounting Bushing Diameter:**

0.453 inches

Jack Contact Arrangement Designator:

J7

#### Mounting Facility Type And Quantity:

2 bushing

## **Terminal Type:**

Tab, solder lug

#### Material:

Steel body

Material:

Steel body

## Precious Material And Location:

Contacts gold and springs silver

Precious Material:

Gold and silver

Surface Treatment:

Nickel bushing

# NSN 5935-01-161-2946

Telephone Jack - Page 2 of 2

Surface Treatment:

Nickel bushing

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A03400

