NSN 5935-01-161-3119

Electrical Receptacle Connector - Page 1 of 2



view Online at https://aerobasegroup.com/hsh/5935-01-161-3119
Body Style:
Straight shape, flush mount
Overall Length:
0.984 inches
Overall Height:
1.687 inches
Overall Width:
3.375 inches
Unthreaded Mounting Hole Diameter:
Between 0.138 inches and 0.145 inches
Center To Center Distance Between Mounting Facilities Parallel To Height:
1.000 inches
Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:
2.875 inches
Distance From Mounting Shoulder To Front Face:
0.078 inches
Mating End Quantity:
1
Contact Position Arrangement Style:
28 single mating end
Contact Removability:
Nonremovable single mating end single contact grouping
Contact Maximum Current Rating In Amps:
20.0 single mating end single contact grouping
Polarization Method:
Mating end
Shell Type:
Solid
Connector Locking Method:
Friction
Terminal Location:
Back single mating end single contact grouping
Contact Material:
Copper alloy single mating end single contact grouping
Contact Surface Treatment:
Gold single mating end single contact grouping and copper single mating end single contact grouping or nickel single mating end single
contact grouping
Insert Material:
Plastic diallyl phthalate single mating end or plastic melamine single mating end

Terminal Type:

Solder well single mating end single contact grouping

Mil-g-45204 military specification 1st treatment response single mating end single contact grouping

Contact Surface Treatment Specification:

NSN 5935-01-161-3119

Fiig: A039b0

Mil-std (military Standard):

Mil-g-45204 spec.

Electrical Receptacle Connector - Page 2 of 2



Contact Material Specification:
Qq-c-533 federal specification single material response single mating end single contact grouping
Shell Material:
Aluminum alloy
Shell Surface Treatment:
Chromate and cadmium
Shell Surface Treatment Specification:
Qq-p-416 type 2, cl 2 federal specification 2nd treatment response
Shell Material Specification:
Qq-a-591/a380 federal specification single material response
Insert Material Specification:
Mil-m-14 ty sdg-f military specification 1st material response single mating end or mil-m-14 ty cmg military specification 2nd material
response single mating end
Included Contact Quantity:
28 single mating end single contact grouping
Included Contact Type:
Round socket single mating end single contact grouping
Precious Material And Location:
Contact surfaces gold
Precious Material And Weight:
0.028 gold grains, troy
Precious Material:
Gold
Shelf Life:
N/a
Unit Of Measure:

Demilitarization:
No