## NSN 5935-01-161-7242

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-161-7242 **Thread Class:** 2a and 2a **Thread Direction:** Right-hand and right-hand **Body Style:** Straight shape, external coupling w/backshell **Overall Length:** 1.703 inches **Overall Height:** 1.281 inches **Overall Width:** 1.281 inches **Environmental Protection:** Heat resistant **Unthreaded Mounting Hole Diameter:** 0.150 inches Center To Center Distance Between Mounting Facilities Parallel To Height: Between 0.964 inches and 0.974 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: Between 0.964 inches and 0.974 inches **Distance From Mounting Shoulder To Front Face:** 0.750 inches **Threaded Device Type:** Back shell and coupling facility **Mating End Quantity:** 1 **Contact Position Arrangement Style:** 16-13 single mating end **Contact Removability:** Nonremovable single mating end single contact grouping **Contact Maximum Current Rating In Amps:** 41.0 single mating end single contact grouping **Contact Maximum Ac Voltage Rating In Volts:** 500.0 single mating end single contact grouping **Contact Maximum Dc Voltage Rating In Volts:** 700.0 single mating end single contact grouping **Polarization Method:** Keyway or multiple keyway **Insert Position In Deg:** 0.0

Shell Type:

Solid

## NSN 5935-01-161-7242

Electrical Receptacle Connector - Page 2 of 2



Connector Locking Method:
Externally threaded shell
Thread Length:
0.375 inches
Thready Qty Per Inch (tpi):
20 and 20
Thread Size:
0.875 inches and 1.000 inches
Terminal Location:
Back single mating end single contact grouping
Contact Material:
Nickel single mating end single contact grouping and nickel alloy single mating end single contact grouping
Insert Material:
Plastic melamine single mating end
Terminal Type:
Solder well single mating end single contact grouping
Shell Material:
Steel
Shell Surface Treatment:
Cadmium and chromate
Included Contact Quantity:
2 single mating end single contact grouping
Included Contact Type:
Round socket single mating end single contact grouping
Thread Series Designator:
Unef and unef
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A039b0