Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-161-7242

Thread Class:

2a and 2a

Thread Direction:

Right-hand and right-hand

Body Style:

Straight shape, external coupling w/backshell

Overall Length:

1.703 inches

Overall Height:

1.281 inches

Overall Width:

1.281 inches

Environmental Protection:

Heat resistant

Unthreaded Mounting Hole Diameter:

0.150 inches

Center To Center Distance Between Mounting Facilities Parallel To Height:

Between 0.964 inches and 0.974 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

Between 0.964 inches and 0.974 inches

Distance From Mounting Shoulder To Front Face:

0.750 inches

Threaded Device Type:

Back shell and coupling facility

Mating End Quantity:

1

Contact Position Arrangement Style:

16-13 single mating end

Contact Removability:

Nonremovable single mating end single contact grouping

Contact Maximum Current Rating In Amps:

41.0 single mating end single contact grouping

Contact Maximum Ac Voltage Rating In Volts:

500.0 single mating end single contact grouping

Contact Maximum Dc Voltage Rating In Volts:

700.0 single mating end single contact grouping

Polarization Method:

Keyway or multiple keyway

Insert Position In Deg:

0.0

Shell Type:

Solid



Connector Locking Method: Externally threaded shell **Thread Length:** 0.375 inches Thready Qty Per Inch (tpi): 20 and 20 **Thread Size:** 0.875 inches and 1.000 inches **Terminal Location:** Back single mating end single contact grouping **Contact Material:** Nickel single mating end single contact grouping and nickel alloy single mating end single contact grouping **Insert Material:** Plastic melamine single mating end **Terminal Type:** Solder well single mating end single contact grouping Shell Material: Steel **Shell Surface Treatment:** Cadmium and chromate **Included Contact Quantity:** 2 single mating end single contact grouping **Included Contact Type:** Round socket single mating end single contact grouping **Thread Series Designator:** Unef and unef Shelf Life: N/a Unit Of Measure: **Demilitarization:** Fiig: A039b0

--

No