Electrical Connector Backshell - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-161-8160

Tread Stoccion:           Right-hand           Overall Legght:           2.812 Inches           Overall Legght:           2.812 Inches           Overall Legght:           2.812 Inches           Overall Legght:           2.812 Inches           Overall Legght:           2.816 Inches           Overall Vidth:           0.898 Inches           Cable Opening Dimeter:           Between 0.125 Inches and 0.250 Inches           Thread Length:           0.210 Inches           Cable Opening Quantity:           1           1 Inced Length:           0.210 Inches           Cable Opening Quantity:           1           1 Inceded coupling           Thread Vay Per Inch (tpl):           24           Cable Opening Countity:           1 Inread Size:           0.888 Inches           Material:           Cable Opening Inceree           Strip Designator:	Thread Class:
Rightradi         Rightradi         Overall Length:         2.312 Inches         Overall Might:         0.750 Inches and 0.250 Inches         Thread Length:         0.750 Inches         10         10         11         11         12         12         12         13         14         14         15         15         16         16         17	
Righ-hand         Overall Height:         2.812 Inches         Overall Height:         0.750 Inches and 0.250 Inches         Bite Descington         2.120 Inches         Overall Height:         0.250 Inches         Old Opening Quantity:         1         Store Descingtion:         2.12         Monting Facility Type And Quantity:         1         1 threaded coupling         Thread Store Inch (tp):         2.4         Norted Store Inch (tp):         2.4         Norted Store Inch (tp):         2.4         Norted Store Inch (tp):         2.4         Store Textment:         1.5         Store Textment:         Store Textme	
Oral Length: 2.812 Indeg 2.812 Indeg 2.812 Indeg 2.812 Indeg 2.821 Indeg 2.720 Indeg	
242 lacks         Overall Wich:         0.750 lacks         1         1         1.750 lacks         0.750 lacks	-
Overall Height:0.750 inches0.750 inches0.750 inches0.590 inches0.590 inches0.590 inches and 0.250 inches0.751 inches and 0.250 inches0.751 inches and 0.250 inches0.715 inches and 0.250 inches0.716 inches and 0.250 inches0.716 inches and 0.250 inches1101111120.726 pasination:1212110.726 pasination:12121212130.726 pasination:1414141415	
0.750 indes Overall Width: 0.969 indes Overall Midth: 0.969 indes Cable Opening Diameter: Cable Opening Diameter: Cable Opening Outorites Thread Length: 0.259 indes Cable Opening Quantity: 0.249 indes Cable Opening Quantity: 1 Stor Designation: 1 1 Mounting Facility Type And Quantity: 1 threadd coupling Thready Diy Per Inch (tpi): 1 1 Autoritum Gale	
Overall Width:         0.949 inches         0.549 inches and 0.250 inches         Chue Opening Diamete:         0.125 inches and 0.250 inches         0.126 inches and 0.250 inches         0.126 inches and 0.250 inches         0.219 inches         Cable Opening Quantity:         0.219 inches         Cable Opening Quantity:         1         Size Designation:         12         Mounting Facility Type And Quantity:         1         1 threadd coupling         Thread Jupy Per Inch (tp):         24         Thread Size:         0.688 inches         Surface Treatment:         Nurikal         Surface Treatment:         Nickel         Surface Treatment:         Nickel Size:         Surface Treatment: <td>-</td>	-
0499 indes 0459 indes 0459 indes 0450 indes	
Beween 0.125 inches         Tread Length:         0.219 inches         Cable Opening Quantity:         1         Size Designation:         12         Mounting Facility Type And Quantity:         1         1 threaded coupling         Thread Size:         0.688 inches         0.688 inches         Murinum alloy         Strafeet Treatment:         Nickel         Syle Designator:         Strafeet Treatment:         Nickel         Syle Designator:         Strafeet Treatment:         Nickel         Strafeet Treatment:         Syle Designator:         Strafeet Treatment:         Nickel         Strafeet Treatment:         Strafeet Treatment:         Nickel         Strafeet Treatment:         Strafeet Treatment:         Nickel         Strafeet Treatment:         Nickel electroless         Strafeet Treatment:         Nickel electroless         Strafeet Treatment:         Nickel electroless         Strafeet Treatment:         Strafeet Treatment:         Nickel electroless<	
Beween 0.125 inches         Tread Length:         0.219 inches         Cable Opening Quantity:         1         Size Designation:         12         Mounting Facility Type And Quantity:         1         1 threadd coupling         Thread Size:         0.688 inches         0.688 inches         Munimu alloy         Strefer Treatment:         Nickel         Syle Designator:         Stradge Strefer Size:         0.688 inches         Murimu alloy         Stradge Treatment:         Nickel         Syle Designator:         Stradge Treatment:         Nickel, electroles         Stradge Sould Space/fication (includes engineering type bulletins, brochures, etc., that reflect specification specification (includes engineering type bulletins, brochures, etc., that reflect specification specification (includes engineering type bulletins, brochures, etc., that reflect specification engineerind type bulletins, brochures, etc., that refl	Cable Opening Diameter:
0.219 inches 0.219 inches 0.220 inches 0.220 inches 1 1 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2	
0.219 inches 0.219 inches 0.221 inches 0.222 inches 1 1 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2	Thread Length:
1         Size Designation:         12         Mounting Facility Type And Quantiy:         1 threaded coupling         Threaded coupling         Threaded size:         0.688 inches         Material:         0.408 inches         Munium alloy         Surface Treatment:         Nickel         Style Designato:         Surface Treatment:         Nickel electroless         Thread Size:         Outrage Treatment:         Nickel electroless         Totaed Size:         Nickel electroless         Totaed Size:         Surface Treatment:         Nickel electroless         Totaed Size:         Surface Treatment:         Nickel electroless         Totaed Size:         Surface Treatment:         Nickel electroless         Totaed Size:         Outraet Treatment:         Nickel electroless         Totaed Size:         Surface Treatment:         Surface Treatment:         Surface Treatment:         Surface Treatment:         Surface Treatment:         Surface Treatment: <td< td=""><td></td></td<>	
Size Designation:         12         Mounting Facility Type And Quantity:         1 threaded coupling         Thready Qty Per Inch (tpi):         24         Thread Size:         0.688 inches         Material:         Autorium alloy         Surface Treatment:         Nickel         Stright type wickable clamp	Cable Opening Quantity:
12 Mounting Facility Type And Quantity: 1 threaded coupling Thready Oty Per Inch (tpi): 24 Thread Size: 0.688 inches Materia: 0.688 inches Materia: Atuminum alloy Surface Treatment: Nickel Surface Treatment: Nickel Style Designator: Straight type w/cable clamp Straight type w/cable clamp Straight type w/cable clamp Straight type w/cable scamp Straight type w/cable scamp	
Nounting Facility Type And Quantity:         1 treaded coupling         Thready Ouy Per Inch (tpi):         24         Thread Size:         0.688 inches         Material:         Aluminum alloy         Surface Treatment:         Nickel         Style Designator:         Sturface Treatment:         Nickel, electroless         Sturface Treatment:         Nickel, electroless         Sturface Treatment:         Nickel, electroless         Sturface Treatment:         Nickel, electroless         Test Data Documential and performance requirements and test conditions that are shown as "typical", "average", ", etc.).         Thread Series Designator:         Unef         Strafes Test Series Designator:         Nickel, electroless         Thread Series Designator:         Strafes Designator: <td< td=""><td>Size Designation:</td></td<>	Size Designation:
۱ threade coupling           Thready Qty Per Inch (tpi):           24           Thread Size:           0.688 inches           Material:           Aluminum alloy           Surface Treatment:           Nickel           Style Designator:           Strafe Treatment:           Nickel           Sturface Treatment:           Nickel           Sturface Treatment:           Nickel, electroles           Sturface Treatment:           Nickel, electroles           Sturface Treatment:           Nickel, electroles, industry directories, and similar trade publications, reflecting general type data on certain           onvironmental and performance requirements and test conditions that are shown as "typical", "average", ", etc.).           Thread Series Designator:           Unef           Strafection Data:           Stady-mil-c-85049/36 government specification           Stady-mil-c-85049/36 government specification           Nickel, Electroles           Stady-mil-c-85049/36 government specification	12
Thready Qty Per Inch (tpi):         24         Thread Size:         0.688 inches         Material:         Aluminum alloy         Surface Treatment:         Nickel         Style Designator:         Stright type w/cable clamp         Surface Treatment:         Nickel, electroless         Test Data Document:         81349-mil-c-85049 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", ", etc.).         Thread Series Designator:         Unef         Specification Data:         81349-mil-c-85049/36 government specification         91349-mil-c-85049/36 government specification         9141 Life:         Na	Mounting Facility Type And Quantity:
24 Tread Size: 0.688 inches Material: Aluminum alloy Surface Treatment: Nickel Style Designator: Straight type w/cable clamp Straight type w/cable clamp Straight type w/cable clamp Straiget treatment: Nickel, electroless Test Data Document: Styles- Stod9 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", ", etc.). Thread Series Designator: Unef Specification Data: Stad9-mil-c-85049/36 government specification Sheff Life: Na	1 threaded coupling
Thread Size:         0.688 inches         Material:         Aluminum alloy         Surface Treatment:         Nickel         Style Designator:         Straight type w/cable clamp         Surface Treatment:         Nickel, electroless         Test Data Document:         81349-mil-c-85049 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification         romat: excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain         rowironmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).         Thread Series Designator:         Unef         Specification Data:         81349-mil-c-85049/36 government specification         Material         Surface Treatment:         Unef         Specification Data:         81349-mil-c-85049/36 government specification         Specification Data:         Nator	Thready Qty Per Inch (tpi):
0.688 inches Material: Aluminum alloy Surface Treatment: Nickel Style Designator: Straight type w/cable clamp Straight type w/cable clamp Surface Treatment: Nickel, electroless Test Data Document: Nickel, electroless Test Data Document: Nickel, electroless, and similar trade publications, reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", ", etc.). Thread Series Designator: Unef Specification Data: 81349-mil-c-85049/36 government specification Sheff Life: Na	24
Material:Aluminum alloySurface Treatment:NickelStyle Designator:Striajcht type w/cable clampSurface Treatment:Nickel, electrolessTest Data Document:81349-mil-c-85049 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specificationromant, excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certainromat, excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certainromat, excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certainromat, excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certainromat, excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certainromat, excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certainromat, excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certainromat, excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certainromat, excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certainromat, excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certainromat, excludes commercial catalogs, industry directories, and similar trade publ	Thread Size:
Aluminum alloy Surface Treatment: Nickel Style Designator: Straight type w/cable clamp Straight type w/cable clamp Surface Treatment: Nickel, electroless Test Data Document: S1349-mil-c-85049 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Thread Series Designator: Unef Specification Data: S1349-mil-c-85049/36 government specification Sheff Life: Na	0.688 inches
Surface Treatment:NickelStyle Designator:Straight type w/cable clampSurface Treatment:Nickel, electrolessTest Data Document:81349-mil-c-85049 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specificationromat; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certainenvironmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).Thread Series Designator:UnefSpecification Data:81349-mil-c-85049/36 government specificationShelf Life:N/a	Material:
Nickel Style Designator: Straight type w/cable clamp Straight type w/cable clamp Surface Treatment: Nickel, electroless Test Data Document: S1349-mil-c-85049 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Thread Series Designator: Unef Specification Data: Shaf Life: N/a	Aluminum alloy
Style Designator:Straight type w/cable clampSurface Treatment:Nickel, electrolessTest Data Document:81349-mil-c-85049 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).Thread Series Designator:UnefSpecification Data:81349-mil-c-85049/36 government specification81349-mil-c-85049/36 government specificationN/a	Surface Treatment:
Straight type w/cable clamp Surface Treatment: Nickel, electroless Test Data Document: 81349-mil-c-85049 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Thread Series Designator: Unef Specification Data: 81349-mil-c-85049/36 government specification Shelf Life: N/a	Nickel
Surface Treatment: Nickel, electroless Test Data Document: 81349-mil-c-85049 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Thread Series Designator: Unef Specification Data: 81349-mil-c-85049/36 government specification Shelf Life: N/a	Style Designator:
Nickel, electroless Test Data Document: 81349-mil-c-85049 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Thread Series Designator: Unef Specification Data: 81349-mil-c-85049/36 government specification Shelf Life: N/a	Straight type w/cable clamp
Test Data Document:         81349-mil-c-85049 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).         Thread Series Designator:         Unef         Specification Data:         81349-mil-c-85049/36 government specification         Shelf Life:         N/a	Surface Treatment:
81349-mil-c-85049 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Thread Series Designator: Unef Specification Data: 81349-mil-c-85049/36 government specification Shelf Life: N/a	Nickel, electroless
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). <b>Thread Series Designator:</b> Unef <b>Specification Data:</b> 81349-mil-c-85049/36 government specification <b>Shelf Life:</b> N/a	Test Data Document:
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). Thread Series Designator: Unef Specification Data: 81349-mil-c-85049/36 government specification Shelf Life: N/a	81349-mil-c-85049 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification
Thread Series Designator:   Unef   Specification Data:   81349-mil-c-85049/36 government specification   Shelf Life:   N/a	format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
Unef Specification Data: 81349-mil-c-85049/36 government specification Shelf Life: N/a	environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Specification Data: 81349-mil-c-85049/36 government specification Shelf Life: N/a	Thread Series Designator:
81349-mil-c-85049/36 government specification Shelf Life: N/a	Unef
Shelf Life: N/a	Specification Data:
N/a	81349-mil-c-85049/36 government specification
	Shelf Life:
Unit Of Measure:	N/a
	Unit Of Measure:

--

Electrical Connector Backshell - Page 2 of 2

Demilitarization:

No

Fiig:

A10100

