NSN 5935-01-161-9574

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-161-9574

Thread Class:
2a
Thread Direction:
Right-hand
Body Style:
Straight shape
Overall Length:
4.100 inches
Overall Width:
0.460 inches
Environmental Protection:
Humidity resistant and salt water resistant and shock resistant and vibration resistant and heat resistant and cold resistant
Distance Between Mounting Facility Centers:
3.700 inches
Threaded Device Type:
Mounting stud
Mating End Quantity:
1
Contact Removability:
Nonremovable single mating end single contact grouping
Contact Maximum Current Rating In Amps:
7.5 single mating end single contact grouping
Polarization Method:
Guide pin/socket
Shell Type:
Solid
Connector Locking Method:
Friction
Thready Qty Per Inch (tpi):
40
Thread Size:
0.112 inches
Terminal Location:
Side single mating end single contact grouping
Contact Material:
Copper alloy single mating end single contact grouping
Contact Surface Treatment:
Gold single mating end single contact grouping
Insert Material:

Contact Surface Treatment Specification:

Plastic diallyl phthalate single mating end and glass fiber single mating end

Mil-g-45204 type 2, cl 1 military specification single treatment response single mating end single contact grouping

NSN 5935-01-161-9574

Mil-g-45204 spec.

Electrical Receptacle Connector - Page 2 of 2



Criticality Code Justification:
Feat
Terminal Type: Discongle mating and single contact grouping
Pin single mating end single contact grouping
Contact Material Specification:
Qq-b-626 federal specification single material response single mating end single contact grouping or qq-b-750 federal specification single
material response single mating end single contact grouping
Shell Material:
Aluminum alloy
Shell Surface Treatment:
Cadmium and chromate
Shell Surface Treatment Specification:
Qq-p-416 type 2, cl 2 federal specification 1st treatment response
Shell Material Specification:
Qq-a-365 federal specification single material response
Insert Material Specification:
Mil-p-19833 ty gdi-30f military specification all material responses single mating end
Unable To Decode:
Unable to decode and unable to decode
Included Contact Quantity:
50 single mating end single contact grouping
Included Contact Type:
Round pin single mating end single contact grouping
Special Features:
Mounted with tw0 0.093 in. Long rivets
Precious Material And Location:
Contact surfaces gold
Precious Material And Weight:
0.050 gold grains, troy
Precious Material:
Gold
Thread Series Designator:
Unc
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A039b0
Mil-std (military Standard):