NSN 5935-01-162-0049



Electrical Receptacle Connector - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5935-01-162-0049 **Body Style:** Straight shape, external coupling **Overall Length:** 0.697 inches **Overall Height:** 1.578 inches **Overall Width:** 1.578 inches **Unthreaded Mounting Hole Diameter:** Between 0.115 inches and 0.130 inches Center To Center Distance Between Mounting Facilities Parallel To Height: 1.250 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: 1.250 inches **Distance From Mounting Shoulder To Front Face:** Between 0.442 inches and 0.447 inches **Mating End Quantity:** 1 **Contact Position Arrangement Style:** 22-55 single mating end **Contact Removability:** Removable single mating end single contact grouping **Contact Maximum Current Rating In Amps:** 10.0 single mating end single contact grouping **Contact Maximum Ac Voltage Rating In Volts:** 500.0 single mating end single contact grouping **Contact Maximum Dc Voltage Rating In Volts:** 700.0 single mating end single contact grouping **Polarization Method:** Keyway or multiple keyway **Insert Position In Deg:** 74.0 Shell Type: Solid **Connector Locking Method:** Bayonet latch **Terminal Location:**

Back single mating end single contact grouping

Contact Material:

Copper alloy single mating end single contact grouping

Insert Material:

Plastic epoxy single mating end

NSN 5935-01-162-0049

Electrical Receptacle Connector - Page 2 of 2



| Terminal Type: |
|--|
| Crimp single mating end single contact grouping |
| Shell Material: |
| Aluminum alloy |
| Shell Surface Treatment: |
| Nickel and cadmium |
| Included Contact Quantity: |
| 55 single mating end single contact grouping |
| Included Contact Type: |
| Round socket single mating end single contact grouping |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |
| A039b0 |
| Mil-std (military Standard): |

Mil-c-38999 spec.