NSN 5935-01-162-4019

Electrical Plug Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-162-4019

Body Style: Straight shape, internal coupling w/strain relief **Body Length:** 1.793 inches **Overall Diameter:** 1.092 inches **Environmental Protection:** Humidity resistant and salt water resistant and shock proof and vibration proof **Cable Entrance Diameter:** 0.375 inches **Mating End Quantity: Contact Position Arrangement Style:** 12-p single mating end **Contact Removability:** Removable single mating end single contact grouping **Polarization Method:** Keyway or multiple keyway **Insert Position In Deg:** 71.0 Shell Type: Solid **Connector Locking Method:** Bayonet latch **Connector Cable Strain Relief Method:** Cable clamp **End Application:** Data gathering set, an/bqh- (v) 4 **Terminal Location:** Back single mating end single contact grouping **Contact Material:** Copper alloy single mating end single contact grouping **Contact Surface Treatment:** Gold single mating end single contact grouping **Insert Material:** Plastic diallyl phthalate single mating end and glass single mating end **Terminal Type:** Crimp single mating end single contact grouping **Shell Material:** Aluminum alloy

Shell Surface Treatment:

Cadmium and chromate

NSN 5935-01-162-4019

Electrical Plug Connector - Page 2 of 2



Shell Material Specification:

Qq-a-591 federal specification single material response

Insert Material Specification:

Mil-m-14, type sdg-f military specification all material responses single mating end

Included Contact Quantity:

12 single mating end single contact grouping

Included Contact Type:

Round pin single mating end single contact grouping

Precious Material And Location:

Contact surfaces gold

Precious Material And Weight:

0.012 gold grains, troy

Precious Material:

Gold

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-m-14 spec.