

View Online at <https://aerobasegroup.com/nsn/5935-01-162-4027>

**Thread Class:**

2a

**Thread Direction:**

Right-hand

**Body Style:**

Straight shape, external coupling

**Overall Length:**

Between 1.037 inches and 1.068 inches

**Overall Height:**

Between 1.980 inches and 2.021 inches

**Overall Width:**

Between 1.980 inches and 2.021 inches

**Environmental Protection:**

Thermal shock resistant and moisture resistant and salt water resistant and shock resistant and vibration resistant

**Unthreaded Mounting Hole Diameter:**

0.177 inches

**Center To Center Distance Between Mounting Facilities Parallel To Height:**

1.562 inches

**Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:**

1.562 inches

**Distance From Mounting Shoulder To Front Face:**

Between 0.859 inches and 0.869 inches

**Threaded Device Type:**

Coupling facility

**Mating End Quantity:**

1

**Shell Type:**

Solid

**Connector Locking Method:**

Externally threaded shell

**End Application:**

1520-01-035-0266

**Thready Qty Per Inch (tpi):**

10

**Thread Size:**

1.750 inches

**Shell Material:**

Aluminum alloy

**Shell Surface Treatment:**

Cadmium and nickel

**Shell Surface Treatment Specification:**

Qq-p-416 ty ii federal specification 1st treatment response and qq-n-290 federal specification 2nd treatment response

**Test Data Document:**

81349-mil-c-22992 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

**Thread Series Designator:**

Double stub

**Specification Data:**

96906-ms18062 government standard

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A039b0

**Mil-std (military Standard):**

Mil-c-22992 spec.