

View Online at <https://aerobasegroup.com/nsn/5935-01-162-4034>

Thread Class:

2g

Thread Direction:

Right-hand

Body Style:

Straight shape, external coupling w/backshell

Overall Length:

2.703 inches

Overall Height:

2.250 inches

Overall Width:

2.250 inches

Unthreaded Mounting Hole Diameter:

0.195 inches

Center To Center Distance Between Mounting Facilities Parallel To Height:

1.687 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

1.687 inches

Distance From Mounting Shoulder To Front Face:

1.188 inches

Threaded Device Type:

Coupling facility

Mating End Quantity:

1

Contact Position Arrangement Style:

16-321 single mating end

Contact Removability:

Nonremovable single mating end single contact grouping

Contact Maximum Current Rating In Amps:

22.0 single mating end single contact grouping

Contact Maximum Ac Voltage Rating In Volts:

500.0 single mating end single contact grouping

Contact Maximum Dc Voltage Rating In Volts:

700.0 single mating end single contact grouping

Polarization Method:

Keyway or multiple keyway

Insert Position In Deg:

0.0

Shell Type:

Solid

Connector Locking Method:

Externally threaded shell

Thread Size:

2.000 inches

Terminal Location:

Back single mating end single contact grouping

Contact Surface Treatment:

Gold single mating end single contact grouping

Terminal Type:

Turret single mating end single contact grouping

Shell Material:

Aluminum alloy 6061

Shell Surface Treatment:

Oxide aluminum

Shell Material Specification:

Qq-a-270 federal specification single material response or qq-a-325 federal specification single material response

Included Contact Quantity:

37 single mating end single contact grouping

Included Contact Type:

Round socket single mating end single contact grouping

Precious Material And Location:

Contact surfaces gold

Precious Material And Weight:

0.037 gold grains, troy

Precious Material:

Gold

Thread Series Designator:

Acme

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A039b0