

View Online at <https://aerobasegroup.com/nsn/5935-01-162-4045>

Thread Class:

2a

Thread Direction:

Right-hand

Body Style:

Straight shape, external coupling

Overall Length:

1.294 inches

Overall Height:

1.766 inches

Overall Width:

1.766 inches

Unable To Decode:

Unable to decode and unable to decode

Environmental Protection:

Corrosion resistant and moisture resistant and vibration resistant

Center To Center Distance Between Mounting Facilities Parallel To Height:

Between 1.250 inches and 1.375 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

Between 1.250 inches and 1.375 inches

Distance From Mounting Shoulder To Front Face:

Between 0.556 inches and 0.587 inches

Threaded Device Type:

Back shell

Mating End Quantity:

1

Polarization Method:

Keyway or multiple keyway

Insert Position In Deg:

0.0

Shell Type:

Solid

Connector Locking Method:

Bayonet pin

Thready Qty Per Inch (tpi):

18

Thread Size:

1.312 inches

Insert Material:

Plastic diallyl phthalate single mating end

Shell Material:

Aluminum alloy

Shell Surface Treatment:

Cadmium

Shell Surface Treatment Specification:

Qq-p-416, type 2, class 3 federal specification single treatment response

Insert Material Specification:

Mil-p-19833, type gdi-30f military specification single material response single mating end or mil-m-14, type sdg-f military specification single material response single mating end

Special Features:

Between mounting slot width 0.120 mils and 0.150 mils

Thread Series Designator:

Unef

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-p-19833 spec.