## NSN 5935-01-162-7931

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-162-7931

View Online at https://aerobasegroup.com/nsn/5935-01-162-7931
Body Style:
Straight shape, external coupling w/backshell
Overall Length:
0.843 inches
Overall Height:
1.578 inches
Overall Width:
1.578 inches
Environmental Protection:
Moisture proof and salt water resistant and vibration proof
Unthreaded Mounting Hole Diameter:
0.120 inches
Center To Center Distance Between Mounting Facilities Parallel To Height:
1.250 inches
Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:
1.250 inches
Distance From Mounting Shoulder To Front Face:
0.447 inches
Mating End Quantity:
1
Contact Position Arrangement Style:
22-21 single mating end
Contact Removability:
Nonremovable single mating end single contact grouping
Polarization Method:
Keyway or multiple keyway
Insert Position In Deg:
0.0
Shell Type:
Solid
Connector Locking Method:
Bayonet pin
Terminal Location:
Back single mating end single contact grouping
Contact Material:
Copper alloy single mating end single contact grouping
Contact Surface Treatment:
Gold single mating end single contact grouping

**Terminal Type:** 

Solder well single mating end single contact grouping

**Shell Material:** 

Aluminum alloy

## NSN 5935-01-162-7931

Electrical Receptacle Connector - Page 2 of 2



Shell Surface Treatment:
Nickel
Shell Surface Treatment Specification:
Mil-c-26074 military specification single treatment response
Included Contact Quantity:
21 single mating end single contact grouping
Included Contact Type:
Round socket single mating end single contact grouping
Precious Material And Location:
Contact surfaces gold
Precious Material And Weight:
0.021 gold grains, troy
Precious Material:
Gold
Test Data Document:
81349-mil-c-38999 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Specification Data:
96906-ms27497 government standard
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A039b0
Mil-std (military Standard):
Mil-c-26074 spec.