NSN 5935-01-162-8605

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-162-8605 **Thread Class:** 2b **Thread Direction:** Right-hand **Body Style:** Straight shape, external coupling **Overall Length:** 4.019 inches **Overall Height:** Between 3.355 inches and 3.396 inches **Overall Width:** Between 3.355 inches and 3.396 inches **Environmental Protection:** Thermal shock resistant and moisture resistant and salt water resistant and shock resistant and vibration resistant **Unthreaded Mounting Hole Diameter:** Between 0.285 inches and 0.296 inches Center To Center Distance Between Mounting Facilities Parallel To Height: 2.812 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: 2.812 inches **Threaded Device Type:** Coupling facility **Mating End Quantity: Contact Removability:** Removable single mating end all contact groupings **Polarization Method:** Keyway or multiple keyway **Insert Position In Deg:** 0.0 Shell Type: **Connector Locking Method:** Externally threaded shell **Thread Size:** 3.000 inches **Terminal Location:**

Back single mating end all contact groupings

Contact Material:

Copper alloy single mating end all contact groupings

Contact Surface Treatment:

Gold single mating end all contact groupings

NSN 5935-01-162-8605

Insert Material:

Electrical Receptacle Connector - Page 2 of 2



Plastic single mating end
Contact Surface Treatment Specification:
Mil-g-45204, type 1, class 1 military specification single treatment response single mating end all contact groupings
Terminal Type:
Crimp single mating end all contact groupings
Shell Material:
Aluminum alloy
Shell Surface Treatment:
Cadmium and nickel
Shell Surface Treatment Specification:
Qq-p-416, type 2 federal specification 1st treatment response and qq-n-290 federal specification 2nd treatment response
Included Contact Quantity:
4 single mating end 3rd contact grouping
Included Contact Type:
Round pin single mating end all contact groupings
Special Features:
Furnished items - protective cover
Precious Material And Location:
Contact surfaces gold
Precious Material And Weight:
0.008 gold grains, troy
Precious Material:
Gold
Thread Series Designator:
Acme
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A039b0
Mil-std (military Standard):
Mil-g-45204 spec.