Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-163-3171

| Thread Clas | 3S: |
|---------------|--|
| 2a | |
| Thread Dire | action: |
| Right-hand | |
| Body Style: | |
| Straight shap | pe, external coupling |
| Overall Len | gth: |
| 1.588 inches | 3 |
| Overall Heig | ght: |
| Between 1.1 | 15 inches and 1.136 inches |
| Overall Wid | th: |
| Between 1.1 | 15 inches and 1.136 inches |
| Environmer | ntal Protection: |
| Corrosion re | sistant and moisture resistant and shock proof and vibration proof |
| Unthreaded | Mounting Hole Diameter: |
| Between 0.1 | 15 inches and 0.125 inches |
| Center To C | Center Distance Between Mounting Facilities Parallel To Height: |
| 0.906 inches | 3 |
| Distance Be | etween Centerlines Of Mounting Facilities Parallel To Body Width: |
| 0.906 inches | 3 |
| Distance Fr | om Mounting Shoulder To Front Face: |
| Between 0.4 | 31 inches and 0.441 inches |
| Threaded D | evice Type: |
| Back shell | |
| Mating End | Quantity: |
| 1 | |
| Contact Pos | sition Arrangement Style: |
| 14-19 single | mating end |
| Contact Rer | movability: |
| Nonremovab | ble single mating end single contact grouping |
| Contact Max | ximum Current Rating In Amps: |
| 7.5 single ma | ating end single contact grouping |
| Contact Ma | ximum Ac Voltage Rating In Volts: |
| 200.0 single | mating end single contact grouping |
| Polarization | |
| Keyway or m | nultiple keyway |
| Insert Posit | |
| 0.0 | - |
| Shell Type: | |
| Solid | |
| | Locking Method: |
| Bayonet pin | |



End Application: Master control set, an/tsq-124a Thready Qty Per Inch (tpi): 20 **Thread Size:** 0.812 inches **Terminal Location:** Back single mating end single contact grouping **Contact Material:** Copper alloy single mating end single contact grouping **Contact Surface Treatment:** Gold single mating end single contact grouping **Insert Material:** Plastic epoxy single mating end and glass single mating end **Terminal Type:** Solder well single mating end single contact grouping **Shell Material:** Aluminum alloy **Shell Surface Treatment:** Cadmium **Included Contact Quantity:** 19 single mating end single contact grouping **Included Contact Type:** Round pin single mating end single contact grouping **Precious Material And Location:** Contact surfaces gold **Precious Material And Weight:** 0.019 gold grains, troy **Precious Material:** Gold **Thread Series Designator:** Unef Shelf Life: N/a Unit Of Measure: --**Demilitarization:** No Fiig: A039b0