Electrical Receptacle Connector - Page 1 of 3



View Online at https://aerobasegroup.com/nsn/5935-01-163-3174

Thread Class:

2a

Thread Direction:

Right-hand

Body Style:

Straight shape, external coupling

Overall Length:

2.012 inches

Overall Height:

1.812 inches

Overall Width:

1.812 inches

Environmental Protection:

Cold resistant and heat resistant and moisture proof and salt water resistant and vibration proof

Unthreaded Mounting Hole Diameter:

Between 0.145 inches and 0.151 inches

Center To Center Distance Between Mounting Facilities Parallel To Height:

1.500 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

1.500 inches

Distance From Mounting Shoulder To Front Face:

0.930 inches

Threaded Device Type:

Back shell

Mating End Quantity:

1

Contact Position Arrangement Style:

24-35 single mating end

Contact Removability:

Removable single mating end single contact grouping

Contact Maximum Current Rating In Amps:

5.0 single mating end single contact grouping

Polarization Method:

Keyway or multiple keyway

Insert Position In Deg:

121.0

Shell Type:

Solid

Connector Locking Method:

Bayonet pin

End Application:

Aircraft, hornet f/a-18

Electrical Receptacle Connector - Page 2 of 3



Thread Length: 0.219 inches Thready Qty Per Inch (tpi): 18 Thread Size: 1.438 inches **Terminal Location:** Back single mating end single contact grouping **Contact Material:** Copper alloy single mating end single contact grouping **Contact Surface Treatment:** Gold single mating end single contact grouping **Contact Surface Treatment Specification:** Mil-g-45204 military specification single treatment response single mating end single contact grouping **Criticality Code Justification:** Feat **Terminal Type:** Crimp single mating end single contact grouping **Shell Material:** Aluminum alloy **Shell Surface Treatment:** Cadmium Shell Surface Treatment Specification: Qq-p-416 federal specification single treatment response **Included Contact Quantity:** 128 single mating end single contact grouping **Included Contact Type:** Round socket single mating end single contact grouping **Special Features:** Weapon system essential **Precious Material And Location:** Contact surfaces gold **Precious Material And Weight:** 0.128 gold grains, troy **Precious Material:** Gold **Thread Series Designator:** Unef Shelf Life: N/a Unit Of Measure: **Demilitarization:** No

Electrical Receptacle Connector - Page 3 of 3



Fiig: A039b0

Mil-std (military Standard):

Mil-g-45204 spec.