# NSN 5935-01-163-7438

Connector Adapter - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-163-7438

#### **Thread Class:**

2a and 2b

**Thread Direction:** 

Right-hand

#### **Body Style:**

Straight shape w/flange

#### **Overall Length:**

1.540 inches

#### **Overall Height:**

1.000 inches

#### **Overall Width:**

1.000 inches

#### **Environmental Protection:**

Heat resistant and shock resistant and vibration resistant

#### **Unthreaded Mounting Hole Diameter:**

#### 0.128 inches

#### Center To Center Distance Between Mounting Facilities Parallel To Height:

0.718 inches

#### Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

0.718 inches

#### Distance From Mounting Shoulder To Front Face:

0.900 inches

#### Threaded Device Type:

Coupling facility

#### Mating End Quantity:

2

#### **Contact Position Arrangement Style:**

Sma 2nd mating end

#### **Contact Removability:**

Nonremovable all mating ends single contact grouping

#### Shell Type:

Solid

## **Connector Locking Method:**

Externally threaded shell and internally threaded shell

## Radio Frequency Type Contact Characteristic Impedance In Ohms:

50.0 all mating ends single contact grouping

### End Application:

6625-01-022-5859

## Thready Qty Per Inch (tpi):

24 and 36

### Thread Size:

0.625 inches and 0.250 inches

## NSN 5935-01-163-7438

Connector Adapter - Page 2 of 2



**Contact Surface Treatment:** Gold all mating ends single contact grouping **Insert Material:** Plastic all mating ends **Contact Surface Treatment Specification:** Mil-g-45204 type 2, cl 2 military specification single treatment response all mating ends single contact grouping Shell Material: Stainless steel **Shell Material Specification:** Qq-s-764, cl 303, cond a federal specification single material response **Insert Material Specification:** Mil-p-19468 military specification single material response all mating ends **Included Contact Quantity:** 1 2nd mating end single contact grouping **Included Contact Type:** Coaxial socket 1st mating end single contact grouping **Precious Material And Location:** Contact surfaces gold **Precious Material And Weight:** 0.010 gold grains, troy **Precious Material:** Gold **Thread Series Designator:** Unef and uns Shelf Life: N/a Unit Of Measure: ---**Demilitarization:** No Fiig: A039b0 Mil-std (military Standard): Mil-g-45204 spec.