NSN 5935-01-163-9342

Electrical Receptacle Connector - Page 1 of 3



View Online at https://aerobasegroup.com/nsn/5935-01-163-9342 **Thread Class:** 2a **Thread Direction:** Right-hand **Body Style:** Straight shape, external coupling **Overall Length:** 1.625 inches **Overall Height:** Between 1.238 inches and 1.278 inches **Overall Width:** Between 1.238 inches and 1.278 inches **Environmental Protection:** Thermal shock resistant and vibration resistant and corrosion resistant and moisture resistant **Unthreaded Mounting Hole Diameter:** Between 0.115 inches and 0.130 inches Center To Center Distance Between Mounting Facilities Parallel To Height: 0.968 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: 0.968 inches **Distance From Mounting Shoulder To Front Face:** Between 0.878 inches and 0.898 inches **Threaded Device Type:** Coupling facility **Mating End Quantity:** 1 **Contact Position Arrangement Style:** 15-21 single mating end **Contact Removability:** Removable single mating end single contact grouping **Polarization Method:** Keyway or multiple keyway **Insert Position In Deg:** 80.0 and 142.0 and 196.0 and 293.0 **Shell Type:** Solid **Connector Locking Method:** Externally threaded shell **End Application:**

An/srq-4

Thread Length:

0.625 inches

NSN 5935-01-163-9342

Electrical Receptacle Connector - Page 2 of 3



Thready Qty Per Inch (tpi):
10
Thread Size:
1.062 inches
Terminal Location:
Back single mating end single contact grouping
Contact Material:
Copper alloy single mating end single contact grouping
Contact Surface Treatment:
Silver single mating end single contact grouping
Insert Material:
Plastic fluorosilicone single mating end
Contact Surface Treatment Specification:
Qq-s-365 1st treatment response clear printed value single mating end single contact grouping
Terminal Type:
Crimp single mating end single contact grouping
Shell Material:
Aluminum alloy
Shell Surface Treatment:
Cadmium
Shell Surface Treatment Specification:
Qq-p-416 federal specification single treatment response
Included Contact Quantity:
21 single mating end single contact grouping
Included Contact Type:
Round pin single mating end single contact grouping
Special Features:
Insert arrangement 15-1; also 20-20 wire size pin in lieu 0f 20-22
Precious Material And Location:
Contact surfaces silver
Precious Material And Weight:
0.021 silver grains, troy
Precious Material:
Silver
Test Data Document:
81349-mil-dtl-28840 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Thread Series Designator:
Double stub
Specification Data:
81349-mil-dtl-28840/12 government specification

Unit Of Measure:

Shelf Life:

N/a

NSN 5935-01-163-9342

Electrical Receptacle Connector - Page 3 of 3



Demilitarization:

No

Fiig:

A039b0