## NSN 5935-01-163-9343

Electrical Receptacle Connector - Page 1 of 3



View Online at https://aerobasegroup.com/nsn/5935-01-163-9343 **Thread Class:** 2a **Thread Direction:** Right-hand **Body Style:** Straight shape, external coupling **Overall Length:** 1.625 inches **Overall Height:** Between 1.698 inches and 1.738 inches **Overall Width:** Between 1.698 inches and 1.738 inches **Environmental Protection:** Thermal shock resistant and vibration resistant and corrosion resistant and moisture resistant **Unthreaded Mounting Hole Diameter:** Between 0.115 inches and 0.130 inches **Center To Center Distance Between Mounting Facilities Parallel To Height:** 1.281 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: 1.281 inches **Distance From Mounting Shoulder To Front Face:** Between 0.878 inches and 0.898 inches **Threaded Device Type:** Coupling facility **Mating End Quantity:** 1 **Contact Position Arrangement Style:** 23-64 single mating end **Contact Removability:** Removable single mating end single contact grouping **Polarization Method:** Keyway or multiple keyway **Insert Position In Deg:** 135.0 and 170.0 and 200.0 and 310.0 **Shell Type:** Solid **Connector Locking Method:** Externally threaded shell **End Application:** 

An/srq-4

Thread Length:

0.625 inches

## NSN 5935-01-163-9343

Demilitarization:

Electrical Receptacle Connector - Page 2 of 3



Thready Qty Per Inch (tpi):
10
Thread Size:
1.500 inches
Terminal Location:
Back single mating end single contact grouping
Contact Material:
Copper alloy single mating end single contact grouping
Contact Surface Treatment:
Silver single mating end single contact grouping
Insert Material:
Plastic epoxy single mating end
Contact Surface Treatment Specification:
Qq-s-365 federal specification single treatment response single mating end single contact grouping
Terminal Type:
Crimp single mating end single contact grouping
Shell Material:
Aluminum alloy
Shell Surface Treatment:
Cadmium
Shell Surface Treatment Specification:
Qq-p-416 federal specification single treatment response
Included Contact Quantity:
64 single mating end single contact grouping
Included Contact Type:
Round socket single mating end single contact grouping
Precious Material And Location:
Contact surfaces silver
Precious Material And Weight:
0.064 silver grains, troy
Precious Material:
Silver
Test Data Document:
81349-mil-dtl-28840/12 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Thread Series Designator:
Double stub
Specification Data:
81349-mil-dtl-28840/12 government specification
Shelf Life:
N/a
Unit Of Measure:

## NSN 5935-01-163-9343

Electrical Receptacle Connector - Page 3 of 3



Fiig:

A039b0