Electrical Receptacle Connector - Page 1 of 3



View Online at https://aerobasegroup.com/nsn/5935-01-163-9345

2a	S:
∠a Thread Direc	tion
Right-hand	
•	
Body Style:	
•	e, external coupling
Overall Leng 1.625 inches	
Overall Heigh	
Overall Width	8 inches and 1.838 inches
	8 inches and 1.838 inches
	al Protection:
	k resistant and vibration resistant and corrosion resistant and moisture resistant
	Mounting Hole Diameter:
	2 inches and 0.157 inches
	enter Distance Between Mounting Facilities Parallel To Height:
1.392 inches	
	ween Centerlines Of Mounting Facilities Parallel To Body Width:
1.392 inches	
	m Mounting Shoulder To Front Face:
	'8 inches and 0.898 inches
Threaded De	
Coupling facili	
Mating End C	Auantity:
1	
	ition Arrangement Style:
G01 single ma	-
Contact Rem	
	ngle mating end single contact grouping
Polarization I	
	ultiple keyway
Insert Positio	on In Deg:
	0.0 and 200.0 and 310.0
Shell Type:	
Solid	
Connector Lo	ocking Method:
Externally thre	eaded shell
End Applicat	ion:
An/srq-4	
Thread Leng	th:

Electrical Receptacle Connector - Page 2 of 3



Thready Qty Per Inch (tpi):

10

Thread Size:

1.625 inches

Terminal Location:

Back single mating end single contact grouping

Contact Material:

Copper alloy single mating end single contact grouping

Contact Surface Treatment:

Silver single mating end single contact grouping

Insert Material:

Plastic epoxy single mating end

Contact Surface Treatment Specification:

Qq-s-365 federal specification single treatment response single mating end single contact grouping

Terminal Type:

Crimp single mating end single contact grouping

Shell Material:

Aluminum alloy

Shell Surface Treatment:

Cadmium

Shell Surface Treatment Specification:

Qq-p-416 federal specification single treatment response

Included Contact Quantity:

92 single mating end single contact grouping

Included Contact Type:

Round pin single mating end single contact grouping

Precious Material And Location:

Contact surfaces silver

Precious Material And Weight:

0.092 silver grains, troy

Precious Material:

Silver

Test Data Document:

81349-mil-c-28840 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Thread Series Designator:

Double stub

Specification Data:

81349-mil-c-28840/12 government specification

Shelf Life:

N/a

Unit Of Measure:

- --
- Demilitarization:

NSN 5935-01-163-9345

Electrical Receptacle Connector - Page 3 of 3

Fiig: A039b0

