

View Online at <https://aerobasegroup.com/nsn/5935-01-164-3597>

**Body Style:**

Straight shape

**Overall Length:**

2.980 inches

**Overall Height:**

1.182 inches

**Overall Width:**

0.300 inches

**Body Length:**

2.060 inches

**Unthreaded Mounting Hole Diameter:**

0.100 inches

**Distance Between Mounting Facility Centers:**

1.900 inches

**Mating End Quantity:**

1

**Contact Position Arrangement Style:**

2 rows of contacts non-inserted board single mating end

**Contact Removability:**

Nonremovable single mating end single contact grouping

**Contact Maximum Current Rating In Amps:**

1.0 single mating end single contact grouping

**Polarization Method:**

Mating end

**Connector Locking Method:**

Latch

**Operating Temperature Rating:**

Between -55.0 degrees celsius and 105.0 degrees celsius

**Terminal Location:**

Back single mating end single contact grouping

**Contact Material:**

Copper alloy single mating end single contact grouping

**Contact Surface Treatment:**

Gold single mating end single contact grouping and nickel single mating end single contact grouping

**Insert Material:**

Plastic polyester glass filled single mating end

**Contact Surface Treatment Specification:**

Mil-g-45204, type 2, grade c military specification 1st treatment response single mating end single contact grouping and qq-n-290, cl 2 federal specification 2nd treatment response single mating end single contact grouping

**Terminal Type:**

Pin single mating end single contact grouping

**Included Contact Quantity:**

26 single mating end single contact grouping

**Included Contact Type:**

Square pin single mating end single contact grouping

**Precious Material And Location:**

Contact surfaces gold

**Precious Material And Weight:**

0.026 gold grains, troy

**Precious Material:**

Gold

**Specification Data:**

00724-16-01514 manufacturers specification control

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A039b0

**Mil-std (military Standard):**

Mil-g-45204 spec.