

View Online at <https://aerobasegroup.com/nsn/5935-01-164-5176>

Body Style:

Straight shape, flush mount

Overall Length:

0.954 inches

Overall Height:

3.110 inches

Overall Width:

2.000 inches

Unthreaded Mounting Hole Diameter:

0.120 inches

Center To Center Distance Between Mounting Facilities Parallel To Height:

2.783 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

1.437 inches

Mating End Quantity:

2

Contact Position Arrangement Style:

40c1 all mating ends

Contact Removability:

Nonremovable all mating ends 1st contact grouping

Contact Maximum Current Rating In Amps:

5.0 all mating ends 1st contact grouping

Polarization Method:

3 polarization posts

Shell Type:

Solid

Connector Locking Method:

Friction

Terminal Location:

Back all mating ends 1st contact grouping

Contact Material:

Copper alloy all mating ends 1st contact grouping

Contact Surface Treatment:

Gold all mating ends 1st contact grouping

Insert Material:

Plastic all mating ends

Contact Surface Treatment Specification:

Mil-g-45204, type 1, grade c, class 1 military specification single treatment response all mating ends 1st contact grouping

Terminal Type:

Solder well all mating ends 1st contact grouping

Guide Design And Location:

Hexagon shape male post left-hand at 12 o'clock and hexagon shape male post center at 12 o'clock and hexagon shape male post right-hand at 12 o'clock

Shell Material:

Aluminum alloy

Shell Surface Treatment:

Cadmium and chromate

Shell Surface Treatment Specification:

Qq-p-416, type 2, class 3 federal specification 1st treatment response

Precious Material And Location:

Contact surfaces gold

Precious Material And Weight:

0.078 gold grains, troy

Precious Material:

Gold

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-g-45204 spec.