# NSN 5935-01-164-5189

Electrical Receptacle Connector - Page 1 of 3



View Online at https://aerobasegroup.com/nsn/5935-01-164-5189
Thread Class:
2a
Thread Direction:
Right-hand
Body Style:
Straight shape, external coupling
Overall Length:
1.405 inches
Overall Height:
1.453 inches
Overall Width:
1.453 inches
Environmental Protection:
Moisture proof and salt water resistant and vibration proof
Unthreaded Mounting Hole Diameter:
0.150 inches
Center To Center Distance Between Mounting Facilities Parallel To Height:
1.125 inches
Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:
1.125 inches
Distance From Mounting Shoulder To Front Face:
Between 0.462 inches and 0.493 inches
Threaded Device Type:
Back shell
Mating End Quantity:
1
Contact Position Arrangement Style:
16-26 single mating end
Contact Removability:
Removable single mating end single contact grouping
Contact Maximum Ac Voltage Rating In Volts:
600.0 single mating end single contact grouping
Polarization Method:
Keyway or multiple keyway
Insert Position In Deg:
0.0
Shell Type:
Solid
Connector Locking Method:
Bayonet pin
Thread Length:

0.290 inches

# NSN 5935-01-164-5189

Electrical Receptacle Connector - Page 2 of 3



# Thready Qty Per Inch (tpi):

20

#### **Thread Size:**

1.000 inches

### **Terminal Location:**

Back single mating end single contact grouping

### **Contact Surface Treatment:**

Gold single mating end single contact grouping and nickel single mating end single contact grouping

#### **Contact Surface Treatment Specification:**

Mil-g-45204 type 1, cl 1, grade c military specification 1st treatment response single mating end single contact grouping and qq-n-290, grade e federal specification 2nd treatment response single mating end single contact grouping

# **Terminal Type:**

Crimp single mating end single contact grouping

### **Shell Material:**

Aluminum alloy 6061

### **Shell Surface Treatment:**

Cadmium

# **Shell Surface Treatment Specification:**

Qq-p-416 federal specification single treatment response

### **Shell Material Specification:**

Qq-a-591 a380 federal specification single material response or qq-a-367, t6 federal specification single material response

# **Included Contact Quantity:**

26 single mating end single contact grouping

#### **Included Contact Type:**

Round socket single mating end single contact grouping

#### **Special Features:**

In order to complete the connector assembly, the user must obtain/provide the backshell; standard versions may be ordered as nsn 5935-01-171-1966, p/n m85049/52-1-16w for the straight style, or nsn 5935-01-186-5611, p/n m85049/51-1-16w for the right angle style

# **Precious Material And Location:**

Contact surfaces gold

#### **Precious Material And Weight:**

0.026 gold grains, troy

# **Precious Material:**

Gold

# Test Data Document:

81349-mil-c-26482 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

# **Thread Series Designator:**

Unef

# **Specification Data:**

96906-ms3472 government standard

### Shelf Life:

N/a

**Unit Of Measure:** 

# NSN 5935-01-164-5189

Electrical Receptacle Connector - Page 3 of 3



Fiig:

A039b0

Mil-std (military Standard):

Mil-g-45204 spec.