Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-165-0698

# **Body Style:** Straight shape, external coupling **Overall Length:** 1.039 inches **Overall Height:** Between 1.011 inches and 1.051 inches **Overall Width:** Between 1.011 inches and 1.051 inches **Environmental Protection:** Moisture proof and salt water resistant and vibration proof **Unthreaded Mounting Hole Diameter:** Between 0.123 inches and 0.138 inches Center To Center Distance Between Mounting Facilities Parallel To Height: 0.812 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: 0.812 inches **Distance From Mounting Shoulder To Front Face:** Between 0.815 inches and 0.820 inches Mating End Quantity: 1 **Contact Position Arrangement Style:** 36100 single mating end **Contact Removability:** Removable single mating end single contact grouping **Polarization Method:** Keyway or multiple keyway **Insert Position In Deg:** 346.0 Shell Type: Solid **Connector Locking Method:** Bayonet pin **End Application:** Radio-telemetric data set, an/srq-4 **Terminal Location:** Back single mating end single contact grouping **Contact Material:** Copper alloy single mating end single contact grouping **Contact Surface Treatment:** Gold single mating end single contact grouping **Terminal Type:**

Crimp single mating end single contact grouping



#### Shell Material:

Aluminum alloy

Shell Surface Treatment:

Cadmium

## Shell Surface Treatment Specification:

Qq-p-416 federal specification single treatment response

### **Included Contact Quantity:**

6 single mating end single contact grouping

### Included Contact Type:

Round pin single mating end single contact grouping

#### **Precious Material And Location:**

Contact surfaces gold

**Precious Material And Weight:** 

0.030 gold grains, troy

#### **Precious Material:**

Gold

#### **Test Data Document:**

81349-mil-c-38999 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain

# environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

#### **Specification Data:**

96906-ms27505 government standard

## Shelf Life:

N/a

## Unit Of Measure:

--

#### Demilitarization:

No

Fiig:

A039b0

#### Mil-std (military Standard):

Mil-c-38999 spec.