Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-165-1807

Body Style:	
Straight shape	
Overall Length:	
7.295 inches	
Overall Width:	
0.490 inches	
Environmental Protection:	
Moisture resistant and shock resistant and vibration resistant	
Unthreaded Mounting Hole Diameter:	
0.122 inches	
Distance Between Mounting Facility Centers:	
6.975 inches	
Mating End Quantity:	
1	
Contact Removability:	
Removable single mating end single contact grouping	
Contact Maximum Current Rating In Amps:	
5.0 single mating end single contact grouping	
Polarization Method:	
Contact to contact polarizing keys	
Terminal Location:	
Back single mating end single contact grouping	
Contact Material:	
Copper alloy single mating end single contact grouping	
Contact Surface Treatment:	
Gold single mating end single contact grouping	
Insert Material:	
Plastic single mating end	
Contact Surface Treatment Specification:	
Mil-g-45204, tyi, grade c, cl 1 military specification single treatment response single mating end single contact grou	uping
Terminal Type:	
Wire wrap single mating end single contact grouping	
Contact Material Specification:	
Qq-c-530 federal specification single material response single mating end single contact grouping	
Included Contact Quantity:	
180 single mating end single contact grouping	
Precious Material And Location:	
Contact surfaces gold	
Precious Material And Weight:	
0.180 gold grains, troy	
Precious Material:	
Gold	

Electrical Receptacle Connector - Page 2 of 2



Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-g-45204 spec.