Electrical Plug Connector - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5935-01-165-2714

| Body Style: |
|---|
| Straight shape w/clamp |
| Overall Height: |
| 3.843 inches |
| Overall Diameter: |
| 2.218 inches |
| Environmental Protection: |
| Vibration resistant |
| Cable Entrance Diameter: |
| Between 0.595 inches and 0.895 inches |
| Mating End Quantity: |
| 1 |
| Contact Removability: |
| Nonremovable single mating end all contact groupings |
| Contact Maximum Current Rating In Amps: |
| 20.0 single mating end all contact groupings |
| Contact Maximum Ac Voltage Rating In Volts: |
| 480.0 single mating end all contact groupings |
| Polarization Method: |
| Contact |
| Connector Locking Method: |
| Contact twistlock |
| Connector Cable Strain Relief Method: |
| Cord grip |
| Terminal Location: |
| Back single mating end all contact groupings |
| Contact Material: |
| Metal single mating end all contact groupings |
| Insert Material: |
| Plastic polyamide single mating end |
| Terminal Type: |
| Screw w/wire lock single mating end all contact groupings |
| Included Contact Quantity: |
| 3 single mating end 3rd contact grouping |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| - |
| Demilitarization: |
| No |
| Fiig: |
| A039b0 |
| - |