Electrical Plug Connector - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5935-01-165-5267



Thread Class:

2b

Thread Direction:

Right-hand

Body Style:

Angle shape, internal coupling

Overall Length:

1.969 inches

Overall Height:

0.969 inches

Overall Diameter:

0.844 inches

Environmental Protection:

Corrosion resistant

Threaded Device Type:

Coupling facility

Mating End Quantity:

1

Contact Position Arrangement Style:

Agab 10-6 single mating end

Contact Removability:

Removable single mating end single contact grouping

Contact Maximum Current Rating In Amps:

7.5 single mating end single contact grouping

Contact Maximum Ac Voltage Rating In Volts:

500.0 single mating end single contact grouping

Contact Maximum Dc Voltage Rating In Volts:

700.0 single mating end single contact grouping

Polarization Method:

Keyway or multiple keyway

Insert Position In Deg:

0.0

Shell Type:

Potting

Connector Locking Method:

Internally threaded coupling ring

Connector Cable Strain Relief Method:

Potting type

Thready Qty Per Inch (tpi):

24

Thread Size:

0.625 inches

NSN 5935-01-165-5267

Electrical Plug Connector - Page 2 of 2



Terminal Location: Back single mating end single contact grouping **Contact Material:** Copper alloy single mating end single contact grouping **Contact Surface Treatment:** Gold single mating end single contact grouping and silver single mating end single contact grouping **Terminal Type:** Crimp single mating end single contact grouping Shell Material: Aluminum alloy **Shell Surface Treatment:** Cadmium and chromate **Included Contact Quantity:** 6 single mating end single contact grouping **Included Contact Type:** Round socket single mating end single contact grouping **Precious Material And Location:** Contact surfaces gold and contact surfaces silver **Precious Material And Weight:** 0.006 gold grains, troy and 0.006 silver grains, troy **Precious Material:** Gold and silver **Thread Series Designator:** Unef Shelf Life: N/a Unit Of Measure: ---**Demilitarization:** No Fiig: A039b0