Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-165-5827

Body Style:

Straight shape, flush mount

Overall Length:

1.326 inches

Overall Height:

2.027 inches

Overall Width:

2.015 inches

Center To Center Distance Between Mounting Facilities Parallel To Height:

1.720 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

1.437 inches

Distance From Mounting Shoulder To Front Face:

0.060 inches

Mating End Quantity:

1

Contact Position Arrangement Style:

67 single mating end

Contact Removability:

Removable single mating end all contact groupings

Contact Maximum Current Rating In Amps:

7.5 single mating end 1st contact grouping

Contact Maximum Ac Voltage Rating In Volts:

1500.0 single mating end 2nd contact grouping

Shell Type:

Solid

Terminal Location:

Back single mating end all contact groupings

Contact Material:

Copper alloy single mating end all contact groupings

Contact Surface Treatment:

Gold single mating end all contact groupings

Insert Material:

Plastic diallyl phthalate single mating end

Contact Surface Treatment Specification:

Mil-g-45204, type ii military specification single treatment response single mating end all contact groupings

Terminal Type:

Crimp single mating end all contact groupings

Contact Material Specification:

Mil-g-45204, type ii military specification single material response single mating end all contact groupings

Shell Material:

Aluminum alloy a380.0

NSN 5935-01-165-5827

Electrical Receptacle Connector - Page 2 of 2



Shell Surface Treatment:
Cadmium
Shell Surface Treatment Specification:
Qq-p-0416, type ii, class 3 federal specification single treatment response
Shell Material Specification:
Qq-a-591 federal specification single material response
Insert Material Specification:
Mil-p-19833, type gd1-30f military specification single material response single mating end
Included Contact Quantity:
67 single mating end all contact groupings
Included Contact Type:
Round socket single mating end all contact groupings
Special Features:
Shipped without sockets
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A039b0
Mil-std (military Standard):

Mil-g-45204 spec.