NSN 5935-01-165-5827

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-165-5827

Body Style:
Straight shape, flush mount
Overall Length:
1.326 inches
Overall Height:
2.027 inches
Overall Width:
2.015 inches
Center To Center Distance Between Mounting Facilities Parallel To Height:
1.720 inches
Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:
1.437 inches
Distance From Mounting Shoulder To Front Face:
0.060 inches
Mating End Quantity:
1
Contact Position Arrangement Style:
67 single mating end
Contact Removability:
Removable single mating end all contact groupings
Contact Maximum Current Rating In Amps:
7.5 single mating end 1st contact grouping
Contact Maximum Ac Voltage Rating In Volts:
1500.0 single mating end 2nd contact grouping
Shell Type:
Solid
Terminal Location:
Back single mating end all contact groupings
Contact Material:
Copper alloy single mating end all contact groupings
Contact Surface Treatment:
Gold single mating end all contact groupings
Insert Material:
Plastic diallyl phthalate single mating end
Contact Surface Treatment Specification:
Mil-g-45204, type ii military specification single treatment response single mating end all contact groupings
Terminal Type:
Crimp single mating end all contact groupings
Contact Material Specification:
Mil-g-45204, type ii military specification single material response single mating end all contact groupings
Shell Material:
Aluminum alloy a380.0

NSN 5935-01-165-5827

Electrical Receptacle Connector - Page 2 of 2



Shell Surface Treatment:
Cadmium
Shell Surface Treatment Specification:
Qq-p-0416, type ii, class 3 federal specification single treatment response
Shell Material Specification:
Qq-a-591 federal specification single material response
Insert Material Specification:
Mil-p-19833, type gd1-30f military specification single material response single mating end
Included Contact Quantity:
67 single mating end all contact groupings
Included Contact Type:
Round socket single mating end all contact groupings
Special Features:
Shipped without sockets
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
Δ039h0

Mil-std (military Standard): Mil-g-45204 spec.