Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-165-8711

Thread	Class:

2a

Thread Direction:

Right-hand

Body Style:

Straight shape

Overall Length:

1.310 inches

Overall Height:

1.140 inches

Overall Width:

0.560 inches

Environmental Protection:

Moisture resistant

Distance Between Mounting Facility Centers:

1.000 inches

Threaded Device Type:

Mounting stud

Mating End Quantity:

1

Contact Position Arrangement Style:

"18, 18-20" single mating end

Contact Removability:

Nonremovable single mating end single contact grouping

Contact Maximum Current Rating In Amps:

7.5 single mating end single contact grouping

Polarization Method:

Guide pin/socket

Connector Locking Method:

Lever-pivot assembly spring action

Thread Length:

0.266 inches

Thready Qty Per Inch (tpi):

40

Thread Size:

0.112 inches

Terminal Location:

Back single mating end single contact grouping

Contact Material:

Copper alloy single mating end single contact grouping

Contact Surface Treatment:

Gold single mating end single contact grouping



Plastic melan	nine mineral filled single mating end
Contact Sur	face Treatment Specification:
Mil-g-45204 r	nilitary specification single treatment response single mating end single contact groupir
Terminal Typ	pe:
Solder well si	ingle mating end single contact grouping
Unable To D	ecode:
Unable to dee	code and unable to decode
Included Co	ntact Quantity:
18 single mat	ting end single contact grouping
Included Co	ntact Type:
Round pin sir	ngle mating end single contact grouping
Special Feat	ures:
Furnished ite	ms - potting form
Precious Ma	terial And Location:
Contact surfa	ices gold
Precious Ma	terial And Weight:
0.018 gold gr	ains, troy
Precious Ma	terial:
Gold	
Thread Serie	es Designator:
Unc	
Shelf Life:	
N/a	
Unit Of Meas	sure:
Demilitarizat	tion:
No	
Fiig:	
A039b0	
Mil-std (milit	ary Standard):
Mil-g-45204 s	spec.