NSN 5935-01-165-9963

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-165-9963
Body Style:
Straight shape
Overall Length:
2.088 inches
Overall Height:
0.833 inches
Overall Width:
Between 0.479 inches and 0.509 inches
Environmental Protection:
Cold resistant and heat resistant
Unthreaded Mounting Hole Diameter:
Between 0.115 inches and 0.125 inches
Distance Between Mounting Facility Centers:
1.852 inches
Mating End Quantity:
1
Contact Position Arrangement Style:
25 single mating end
Contact Removability:
Removable single mating end single contact grouping
Contact Maximum Current Rating In Amps:
3.0 single mating end single contact grouping
Polarization Method:
Mating end
Shell Type:
Solid
Connector Locking Method:
Friction
End Application:
An/trc-170
Terminal Location:
Back single mating end single contact grouping
Contact Material:
Copper alloy single mating end single contact grouping
Contact Surface Treatment:
Gold single mating end single contact grouping and nickel single mating end single contact grouping
Insert Material:
Plastic single mating end and glass fiber single mating end
Contact Surface Treatment Specification:
Mil-g-45204 type 2, cl 1, grade c or d military specification 1st treatment response single mating end single contact grouping and qq-n-290
federal specification 2nd treatment response single mating end single contact grouping

Terminal Type:

Crimp single mating end single contact grouping

NSN 5935-01-165-9963

Electrical Receptacle Connector - Page 2 of 2



Contact Material Specification:
Qq-b-626 federal specification single material response single mating end single contact grouping
Shell Material:
Steel
Shell Surface Treatment:
Chromate and cadmium
Shell Surface Treatment Specification:
Qq-p-416 federal specification all treatment responses
Shell Material Specification:
Qq-s-698 federal specification single material response
Included Contact Quantity:
25 single mating end single contact grouping
Included Contact Type:
Round socket single mating end single contact grouping
Precious Material And Location:
Contact surfaces gold
Precious Material And Weight:
0.025 gold grains, troy
Precious Material:
Gold
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiia:

A039b0

Mil-std (military Standard):

Mil-g-45204 spec.