## NSN 5935-01-166-2871

Electrical Plug Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-166-2871 **Thread Class:** 2b **Thread Direction:** Right-hand **Body Style:** Straight shape, internal coupling **Overall Length:** 1.030 inches **Overall Diameter:** 0.380 inches **Environmental Protection:** Heat resistant and cold resistant and vibration resistant and shock resistant and salt water resistant and moisture resistant **Cable Entrance Diameter:** 0.220 inches **Threaded Device Type:** Coupling facility **Mating End Quantity:** 1 **Contact Position Arrangement Style:** Sma single mating end **Contact Removability:** Removable single mating end single contact grouping

### **Contact Maximum Frequency Rating:**

12400.0 megahertz single mating end single contact grouping

### Shell Type:

Solid

### **Connector Locking Method:**

Internally threaded shell

### **Connector Cable Strain Relief Method:**

Crimp type

### Radio Frequency Type Contact Characteristic Impedance In Ohms:

50.0 single mating end single contact grouping

### Thready Qty Per Inch (tpi):

36

### **Thread Size:**

0.250 inches

### **Terminal Location:**

Back single mating end single contact grouping

### **Contact Material:**

Copper alloy single mating end single contact grouping

### **Contact Surface Treatment:**

Gold single mating end single contact grouping

# NSN 5935-01-166-2871

Electrical Plug Connector - Page 2 of 2



Insert Material:
Plastic polytetrafluoroethylene single mating end
Contact Surface Treatment Specification:
Mil-g-45204 type 2, cl 2 military specification single treatment response single mating end single contact grouping
Terminal Type:
Crimp single mating end single contact grouping
Contact Material Specification:
Qq-b-626 alloy 360 federal specification single material response single mating end single contact grouping
Shell Material:
Copper alloy
Shell Surface Treatment:
Gold
Shell Surface Treatment Specification:
Mil-g-45204 type 2, cl 2 military specification single treatment response
Shell Material Specification:
Qq-c-530 federal specification single material response
Insert Material Specification:
L-p-403 federal specification single material response single mating end
Included Contact Quantity:
1 single mating end single contact grouping
Included Contact Type:
Coaxial pin single mating end single contact grouping
Special Features:
Flange has 3 holes each 0.025 in. Diameter
Precious Material And Location:
Contact and body surfaces gold
Precious Material And Weight:
0.105 gold grains, troy
Precious Material:
Gold
Thread Series Designator:
Uns
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Mil-std (military Standard): Mil-g-45204 spec.

Fiig: A039b0