

View Online at <https://aerobasegroup.com/nsn/5935-01-166-2877>

Body Style:

Straight type

Overall Length:

2.590 inches

Overall Width:

0.440 inches

Unthreaded Mounting Hole Diameter:

0.144 inches

Distance Between Mounting Facility Centers:

2.188 inches

Mating End Quantity:

1

Contact Position Arrangement Style:

2 rows of contacts non-inserted board single mating end

Contact Removability:

Nonremovable single mating end single contact grouping

Contact Maximum Current Rating In Amps:

7.5 single mating end single contact grouping

Contact Maximum Dc Voltage Rating In Volts:

725.0 single mating end single contact grouping

Polarization Method:

Shell

Connector Locking Method:

Friction

Terminal Location:

Back single mating end single contact grouping

Contact Material:

Copper alloy single mating end single contact grouping

Contact Surface Treatment:

Gold single mating end single contact grouping

Insert Material:

Plastic diallyl phthalate single mating end

Terminal Type:

Turret single mating end single contact grouping

Insert Material Specification:

Mil-m-14 ty mdg military specification single material response single mating end

Shell Guide Type And Location Designator:

A slot and c slot

Included Contact Quantity:

11 single mating end single contact grouping

Included Contact Type:

Round socket single mating end single contact grouping

Precious Material And Location:

Contact surfaces gold

Precious Material And Weight:

0.011 gold grains, troy

Precious Material:

Gold

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-m-14 spec.