Electrical Connector Backshell - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5935-01-167-1644

Thread Direction:         Right-hand         Overall Length:         2.125 inches         Overall Height:         1.125 inches         Overall Width:         0.875 inches         Cable Opening Diameter:         Between 0.375 inches and 0.500 inches         Cable Opening Quantity:         1         Size Designation:         10 and 11         Mounting Facility Type And Quantity:         1 threaded coupling         Thread Size:         15.0 millimeters         Thread Pitch In Millimeters:         1.00         Thread Tolerance Class:         6h internal         Material:         Aluminum alloy         Surface Treatment:         Cadmium and nickel         Stright type w/cable clamp         Surface Treatment:         Cadmium and nickel, electroless         Thread Series Designator:         Iso s         Shelf Life:         N/a         Unit Of Measure:            Pemilitarization:	
Overall Length:2.125 inchesOverall Height:1.125 inchesOverall Width:0.875 inchesCable Opening Diameter:Between 0.375 inches and 0.500 inchesCable Opening Quantity:1Size Designation:10 and 11Mounting Facility Type And Quantity:1 threaded couplingThread Size:15.0 millimetersThread Pitch In Millimeters:1.00Thread Tolerance Class:6h internalMaterial:Aluminum alloySurface Treatment:Cadmium and nickelStraight type w/cable clampSurface Treatment:Cadmium and nickel, electrolessThread Series Designator:Iso sShelf Life:N/aUnit Of Measure:Demilitarization:	Thread Direction:
2.125 inches Overall Height: 1.125 inches Overall Width: 0.875 inches Cable Opening Diameter: Between 0.375 inches and 0.500 inches Cable Opening Quantity: Between 0.375 inches and 0.500 inches Cable Opening Quantity: 1 Size Designation: 10 and 11 Mounting Facility Type And Quantity: 10 and 11 Mounting Facility Type And Quantity: 1 threaded coupling Thread Size: 15.0 millimeters Thread Pitch In Millimeters: 1.00 Thread Tolerance Class: 6h internal Material: Aluminum alloy Surface Treatment: Cadmium and nickel Style Designator: Straight type w/cable clamp Surface Treatment: Cadmium and nickel, electroless Thread Series Designator: Iso s Shelf Life: N/a Unit Of Measure:	Right-hand
Overall Height:1.125 inchesOverall Width:0.875 inchesCable Opening Diameter:Between 0.375 inches and 0.500 inchesCable Opening Quantity:1Size Designation:10 and 11Mounting Facility Type And Quantity:1 threaded couplingThread Size:15.0 millimetersThread Pitch In Millimeters:1.00Thread Tolerance Class:6h internalMaterial:Aluminum alloySurface Treatment:Cadmium and nickelStraight type w/cable clampSurface Treatment:Cadmium and nickel, electrolessThread Series Designator:Iso sShelf Life:N/aUnit Of Measure:Demilitarization:	Overall Length:
1.125 inches Overall Width: 0.875 inches Cable Opening Diameter: Between 0.375 inches and 0.500 inches Cable Opening Quantity: 1 Size Designation: 10 and 11 Mounting Facility Type And Quantity: 1 threaded coupling Thread Size: 15.0 millimeters Thread Pitch In Millimeters: 1.00 Thread Tolerance Class: 6 hinternal Material: Aluminum alloy Surface Treatment: Cadmium and nickel Style Designator: Straight type w/cable clamp Surface Treatment: Cadmium and nickel, electroless Thread Series Designator: Iso s Shelf Life: N/a Unit Of Measure:	2.125 inches
Overall Width:0.875 inchesCable Opening Diameter:Between 0.375 inches and 0.500 inchesCable Opening Quantity:1Size Designation:10 and 11Mounting Facility Type And Quantity:1 threaded couplingThread Size:15.0 millimetersThread Pitch In Millimeters:1.00Thread Tolerance Class:6h internalMaterial:Aluminum alloySurface Treatment:Cadmium and nickelStyle Designator:Straight type w/cable clampSurface Treatment:Cadmium and nickel, electrolessThread Series Designator:Iso sShelf Life:N/aUnit Of Measure:-Demilitarization:	Overall Height:
0.875 inches Cable Opening Diameter: Between 0.375 inches and 0.500 inches Cable Opening Quantity: 1 Size Designation: 10 and 11 Mounting Facility Type And Quantity: 1 threaded coupling Thread Size: 15.0 millimeters Thread Pitch In Millimeters: 1.00 Thread Tolerance Class: 6h internal Material: Aluminum alloy Surface Treatment: Cadmium and nickel Style Designator: Straight type w/cable clamp Surface Treatment: Cadmium and nickel, electroless Thread Series Designator: Iso s Shelf Life: N/a Unit Of Measure: 	1.125 inches
Cable Opening Diameter: Between 0.375 inches and 0.500 inches Cable Opening Quantity: 1 Size Designation: 10 and 11 Mounting Facility Type And Quantity: 1 threaded coupling Thread Size: 15.0 millimeters Thread Pitch In Millimeters: 1.00 Thread Tolerance Class: 6h internal Material: Aluminum alloy Surface Treatment: Cadmium and nickel Style Designator: Straight type w/cable clamp Surface Treatment: Cadmium and nickel, electroless Thread Series Designator: Iso s Shelf Life: N/a Unit Of Measure: 	Overall Width:
Between 0.375 inches and 0.500 inches Cable Opening Quantity: 1 Size Designation: 10 and 11 Mounting Facility Type And Quantity: 1 threaded coupling Thread Size: 15.0 millimeters Thread Pitch In Millimeters: 1.00 Thread Tolerance Class: 6h internal Material: Aluminum alloy Surface Treatment: Cadmium and nickel Style Designator: Straight type w/cable clamp Surface Treatment: Cadmium and nickel, electroless Thread Series Designator: Iso s Shelf Life: N/a Unit Of Measure: 	0.875 inches
Cable Opening Quantity:   1   Size Designation:   10 and 11   Mounting Facility Type And Quantity:   1 threaded coupling   Thread Size:   15.0 millimeters   Thread Pitch In Millimeters:   1.00   Thread Tolerance Class:   6h internal   Material:   Aluminum alloy   Surface Treatment:   Cadmium and nickel   Style Designator:   Straight type w/cable clamp   Surface Treatment:   Cadmium and nickel, electroless   Thread Series Designator:   Iso s   Shelf Life:   N/a   Unit Of Measure:     Demilitarization:	Cable Opening Diameter:
1         Size Designation:         10 and 11         Mounting Facility Type And Quantity:         1 threaded coupling         Thread Size:         15.0 millimeters         Thread Pitch In Millimeters:         1.00         Thread Tolerance Class:         6h internal         Material:         Aluminum alloy         Surface Treatment:         Cadmium and nickel         Straight type w/cable clamp         Surface Treatment:         Cadmium and nickel, electroless         Thread Series Designator:         Iso s         Shelf Life:         N/a         Unit Of Measure:         -         Demilitarization:	Between 0.375 inches and 0.500 inches
Size Designation: 10 and 11 Mounting Facility Type And Quantity: 1 threaded coupling Thread Size: 15.0 millimeters Thread Pitch In Millimeters: 1.00 Thread Tolerance Class: 6h internal Material: Aluminum alloy Surface Treatment: Cadmium and nickel Style Designator: Straight type w/cable clamp Surface Treatment: Cadmium and nickel, electroless Thread Series Designator: Iso s Shelf Life: N/a Unit Of Measure: 	Cable Opening Quantity:
10 and 11 Mounting Facility Type And Quantity: 1 threaded coupling Thread Size: 15.0 millimeters Thread Pitch In Millimeters: 1.00 Thread Tolerance Class: 6h internal Material: Aluminum alloy Surface Treatment: Cadmium and nickel Style Designator: Straight type w/cable clamp Surface Treatment: Cadmium and nickel, electroless Thread Series Designator: Iso s Shelf Life: N/a Unit Of Measure: 	1
Mounting Facility Type And Quantity: 1 threaded coupling Thread Size: 15.0 millimeters Thread Pitch In Millimeters: 1.00 Thread Tolerance Class: 6h internal Material: Aluminum alloy Surface Treatment: Cadmium and nickel Style Designator: Straight type w/cable clamp Surface Treatment: Cadmium and nickel, electroless Thread Series Designator: Iso s Shelf Life: N/a Unit Of Measure: 	Size Designation:
1 threaded coupling Thread Size: 15.0 millimeters Thread Pitch In Millimeters: 1.00 Thread Tolerance Class: 6h internal Material: Aluminum alloy Surface Treatment: Cadmium and nickel Style Designator: Straight type w/cable clamp Surface Treatment: Cadmium and nickel, electroless Thread Series Designator: Iso s Shelf Life: N/a Unit Of Measure: 	10 and 11
Thread Size: 15.0 millimeters Thread Pitch In Millimeters: 1.00 Thread Tolerance Class: 6h internal Material: Aluminum alloy Surface Treatment: Cadmium and nickel Style Designator: Straight type w/cable clamp Surface Treatment: Cadmium and nickel, electroless Thread Series Designator: Iso s Shelf Life: N/a Unit Of Measure: 	Mounting Facility Type And Quantity:
15.0 millimeters Thread Pitch In Millimeters: 1.00 Thread Tolerance Class: 6h internal Material: Aluminum alloy Surface Treatment: Cadmium and nickel Style Designator: Straight type w/cable clamp Surface Treatment: Cadmium and nickel, electroless Thread Series Designator: Iso s Shelf Life: N/a Unit Of Measure: Demilitarization:	1 threaded coupling
Thread Pitch In Millimeters: 1.00 Thread Tolerance Class: 6h internal Material: Aluminum alloy Surface Treatment: Cadmium and nickel Style Designator: Straight type w/cable clamp Surface Treatment: Cadmium and nickel, electroless Thread Series Designator: Iso s Shelf Life: N/a Unit Of Measure:  Demilitarization:	Thread Size:
1.00 Thread Tolerance Class: 6h internal Material: Aluminum alloy Surface Treatment: Cadmium and nickel Style Designator: Straight type w/cable clamp Surface Treatment: Cadmium and nickel, electroless Thread Series Designator: Iso s Shelf Life: N/a Unit Of Measure: 	15.0 millimeters
Thread Tolerance Class: 6h internal Material: Aluminum alloy Surface Treatment: Cadmium and nickel Style Designator: Straight type w/cable clamp Surface Treatment: Cadmium and nickel, electroless Thread Series Designator: Iso s Shelf Life: N/a Unit Of Measure:  Demilitarization:	Thread Pitch In Millimeters:
6h internal Material: Aluminum alloy Surface Treatment: Cadmium and nickel Style Designator: Straight type w/cable clamp Surface Treatment: Cadmium and nickel, electroless Thread Series Designator: Iso s Shelf Life: N/a Unit Of Measure:  Demilitarization:	1.00
Material:Aluminum alloySurface Treatment:Cadmium and nickelStyle Designator:Straight type w/cable clampSurface Treatment:Cadmium and nickel, electrolessThread Series Designator:Iso sShelf Life:N/aUnit Of Measure:Demilitarization:	Thread Tolerance Class:
Aluminum alloy Surface Treatment: Cadmium and nickel Style Designator: Straight type w/cable clamp Surface Treatment: Cadmium and nickel, electroless Thread Series Designator: Iso s Shelf Life: N/a Unit Of Measure: Demilitarization:	6h internal
Surface Treatment: Cadmium and nickel Style Designator: Straight type w/cable clamp Surface Treatment: Cadmium and nickel, electroless Thread Series Designator: Iso s Shelf Life: N/a Unit Of Measure: 	Material:
Cadmium and nickel Style Designator: Straight type w/cable clamp Surface Treatment: Cadmium and nickel, electroless Thread Series Designator: Iso s Shelf Life: N/a Unit Of Measure: Demilitarization:	Aluminum alloy
Style Designator: Straight type w/cable clamp Surface Treatment: Cadmium and nickel, electroless Thread Series Designator: Iso s Shelf Life: N/a Unit Of Measure:  Demilitarization:	Surface Treatment:
Straight type w/cable clamp Surface Treatment: Cadmium and nickel, electroless Thread Series Designator: Iso s Shelf Life: N/a Unit Of Measure:  Demilitarization:	Cadmium and nickel
Surface Treatment: Cadmium and nickel, electroless Thread Series Designator: Iso s Shelf Life: N/a Unit Of Measure:  Demilitarization:	Style Designator:
Cadmium and nickel, electroless Thread Series Designator: Iso s Shelf Life: N/a Unit Of Measure:  Demilitarization:	Straight type w/cable clamp
Thread Series Designator: Iso s Shelf Life: N/a Unit Of Measure:  Demilitarization:	Surface Treatment:
Iso s Shelf Life: N/a Unit Of Measure: Demilitarization:	Cadmium and nickel, electroless
Shelf Life: N/a Unit Of Measure:  Demilitarization:	Thread Series Designator:
N/a Unit Of Measure:  Demilitarization:	lso s
Unit Of Measure:  Demilitarization:	Shelf Life:
 Demilitarization:	N/a
	Unit Of Measure:
No	Demilitarization:
	No
Fiig:	Fiig:
A10100	A10100