NSN 5935-01-167-3183

Thread Class:

Thread Direction:

2b

Electrical Plug Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-167-3183

Right-hand
Body Style:
Straight shape, internal coupling w/strain relief
Body Length:
2.952 inches
Overall Diameter:
1.571 inches
Cable Entrance Diameter:
0.622 inches
Threaded Device Type:
Coupling facility
Mating End Quantity:
1
Contact Position Arrangement Style:
20-27 single mating end
Contact Removability:
Nonremovable single mating end single contact grouping
Polarization Method:
Keyway or multiple keyway
Insert Position In Deg:
Insert Position In Deg: 0.0
_
0.0
0.0 Shell Type:
0.0 Shell Type: Solid
0.0 Shell Type: Solid Connector Locking Method:
0.0 Shell Type: Solid Connector Locking Method: Internally threaded coupling ring
0.0 Shell Type: Solid Connector Locking Method: Internally threaded coupling ring Connector Cable Strain Relief Method:
0.0 Shell Type: Solid Connector Locking Method: Internally threaded coupling ring Connector Cable Strain Relief Method: Cable clamp
0.0 Shell Type: Solid Connector Locking Method: Internally threaded coupling ring Connector Cable Strain Relief Method: Cable clamp End Application:
O.0 Shell Type: Solid Connector Locking Method: Internally threaded coupling ring Connector Cable Strain Relief Method: Cable clamp End Application: 6920-01-m13-8642
O.0 Shell Type: Solid Connector Locking Method: Internally threaded coupling ring Connector Cable Strain Relief Method: Cable clamp End Application: 6920-01-m13-8642 Thready Qty Per Inch (tpi):
O.0 Shell Type: Solid Connector Locking Method: Internally threaded coupling ring Connector Cable Strain Relief Method: Cable clamp End Application: 6920-01-m13-8642 Thready Qty Per Inch (tpi): 18
Shell Type: Solid Connector Locking Method: Internally threaded coupling ring Connector Cable Strain Relief Method: Cable clamp End Application: 6920-01-m13-8642 Thready Qty Per Inch (tpi): 18 Thread Size:
Shell Type: Solid Connector Locking Method: Internally threaded coupling ring Connector Cable Strain Relief Method: Cable clamp End Application: 6920-01-m13-8642 Thready Qty Per Inch (tpi): 18 Thread Size: 1.250 inches
Shell Type: Solid Connector Locking Method: Internally threaded coupling ring Connector Cable Strain Relief Method: Cable clamp End Application: 6920-01-m13-8642 Thready Qty Per Inch (tpi): 18 Thread Size: 1.250 inches Terminal Location:
Shell Type: Solid Connector Locking Method: Internally threaded coupling ring Connector Cable Strain Relief Method: Cable clamp End Application: 6920-01-m13-8642 Thready Qty Per Inch (tpi): 18 Thread Size: 1.250 inches Terminal Location: Back single mating end single contact grouping

Silver single mating end single contact grouping

NSN 5935-01-167-3183Electrical Plug Connector - Page 2 of 2



insert Material:
Plastic single mating end
Terminal Type:
Solder well single mating end single contact grouping
Shell Material:
Aluminum alloy
Shell Surface Treatment:
Chromate
Included Contact Quantity:
14 single mating end single contact grouping
Included Contact Type:
Round pin single mating end single contact grouping
Precious Material And Location:
Contact surfaces silver
Precious Material And Weight:
0.014 silver grains, troy
Precious Material:
Silver
Thread Series Designator:
Unef
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A039b0