NSN 5935-01-167-3384

Body Style:

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-167-3384

Right angle type
Overall Length:
8.900 inches
Overall Width:
0.755 inches
Body Height:
0.250 inches
Environmental Protection:
Salt water resistant and humidity resistant and thermal shock resistant and vibration resistant
Unthreaded Mounting Hole Diameter:
0.095 inches
Distance Between Mounting Facility Centers:
8.600 inches
Mating End Quantity:
1
Contact Position Arrangement Style:
1 row of contacts non-inserted board single mating end
Contact Removability:
Nonremovable single mating end single contact grouping
Contact Maximum Current Rating In Amps:
3.0 single mating end single contact grouping
Contact Maximum Ac Voltage Rating In Volts:
1000.0 single mating end single contact grouping
Polarization Method:
Guide pin/socket
Terminal Location:
Side single mating end single contact grouping
Contact Material:
Copper alloy single mating end single contact grouping
Contact Surface Treatment:
Nickel single mating end single contact grouping
Insert Material:
Plastic polyamide single mating end
Contact Surface Treatment Specification:
Qq-n-290 federal specification single treatment response single mating end single contact grouping
Terminal Type:
Pin single mating end single contact grouping
in single mating and single contact grouping

Guide Design And Location:

Hexagon shape male post left-hand at 3 oclock and hexagon shape male post right-hand at 3 oclock

Qq-c-533 federal specification single material response single mating end single contact grouping

NSN 5935-01-167-3384

Electrical Receptacle Connector - Page 2 of 2



Insert Material Specification:

Mil-m-20693 military specification single material response single mating end

Included Contact Quantity:

80 single mating end single contact grouping

Included Contact Type:

Round pin single mating end single contact grouping

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-m-20693 spec.