## NSN 5935-01-167-3387

**Body Style:** 

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-167-3387

Right angle type
Overall Length:
8.900 inches
Overall Width:
0.755 inches
Body Height:
0.250 inches
Environmental Protection:
Salt water resistant and humidity resistant and thermal shock resistant and vibration resistant
Unthreaded Mounting Hole Diameter:
0.095 inches
Distance Between Mounting Facility Centers:
8.600 inches
Mating End Quantity:
1
Contact Position Arrangement Style:
1 row of contacts non-inserted board single mating end
Contact Removability:
Nonremovable single mating end single contact grouping
Contact Maximum Current Rating In Amps:
3.0 single mating end single contact grouping
Contact Maximum Ac Voltage Rating In Volts:
1000.0 single mating end single contact grouping
Polarization Method:
Guide pin/socket
Terminal Location:
Side single mating end single contact grouping
Contact Material:
Copper alloy single mating end single contact grouping
Contact Surface Treatment:
Nickel single mating end single contact grouping
Insert Material:
Plastic polyamide single mating end
Contact Surface Treatment Specification:
Qq-n-290 federal specification single treatment response single mating end single contact grouping
Terminal Type:
Pin single mating end single contact grouping
Contact Material Specification:

Qq-c-533 federal specification single material response single mating end single contact grouping

**Guide Design And Location:** 

Hexagon shape male post right-hand at 1 oclock

## NSN 5935-01-167-3387

Electrical Receptacle Connector - Page 2 of 2



## **Insert Material Specification:**

Mil-m-26093 military specification single material response single mating end

**Included Contact Quantity:** 

80 single mating end single contact grouping

**Included Contact Type:** 

Round pin single mating end single contact grouping

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-m-26093 spec.