NSN 5935-01-167-5119

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-167-5119

Body Style: Straight edge type w/mounting flange **Overall Length:** 5.805 inches **Overall Height:** 1.285 inches **Overall Width:** 0.325 inches **Unthreaded Mounting Hole Diameter:** 0.156 inches **Distance Between Mounting Facility Centers:** 5.545 inches **Board Accommodated Length:** 5.125 inches single board **Board Accommodated Width:** 0.062 inches **Mating End Quantity: Contact Position Arrangement Style:** 2 rows of independent contacts inserted board single mating end **Contact Removability:** Nonremovable single mating end single contact grouping **Contact Maximum Current Rating In Amps:** 3.0 single mating end single contact grouping **Polarization Method:** Contact to contact polarizing keys **Connector Locking Method:** Friction **Terminal Location:** Back single mating end single contact grouping **Contact Material:** Copper alloy single mating end single contact grouping **Contact Surface Treatment:** Gold single mating end single contact grouping and nickel single mating end single contact grouping **Insert Material:** Plastic diallyl phthalate single mating end **Terminal Type:** Wire wrap single mating end single contact grouping **Contact Material Specification:**

Insert Material Specification:

Mil-m-14, type sdgf military specification single material response single mating end

Qq-w-321 federal specification single material response single mating end single contact grouping

NSN 5935-01-167-5119

Electrical Receptacle Connector - Page 2 of 2



Included Contact Quantity:
80 single mating end single contact grouping
Included Contact Type:
Bifurcated spring single mating end single contact grouping
Precious Material And Location:
Contact surfaces gold
Precious Material And Weight:
0.080 gold grains, troy
Precious Material:
Gold
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A039b0

Mil-std (military Standard):

Mil-m-14 spec.