NSN 5935-01-167-5120

Plastic diallyl phthalate single mating end

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-167-5120 **Thread Class:** 2b **Thread Direction:** Right-hand **Body Style:** Rectangular shape **Overall Length:** 2.592 inches Center To Center Distance Between Mounting Facilities Parallel To Length: 2.280 inches **Overall Height:** 0.798 inches **Overall Width:** 0.900 inches **Environmental Protection:** Corrosion resistant and humidity resistant and shock resistant and vibration resistant **Unthreaded Mounting Hole Diameter:** 0.125 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: 0.468 inches **Threaded Device Type:** Coupling facility **Mating End Quantity: Contact Removability:** Removable single mating end single contact grouping **Polarization Method:** Guide pin/socket **Connector Locking Method:** Screw Thready Qty Per Inch (tpi): **Thread Size:** 0.125 inches **Terminal Location:** Back single mating end single contact grouping **Contact Material:** Copper alloy single mating end single contact grouping **Contact Surface Treatment:** Gold single mating end single contact grouping and nickel single mating end single contact grouping **Insert Material:**

NSN 5935-01-167-5120

Electrical Receptacle Connector - Page 2 of 2



Contact Surface Treatment Specification:

Mil-g-45204, ty ii grade d, cl 1 military specification 1st treatment response single mating end single contact grouping and qq-n-290, cl 2 federal specification 2nd treatment response single mating end single contact grouping

Terminal Type:

Wire wrap single mating end single contact grouping

Contact Material Specification:

Qq-b-750 federal specification single material response single mating end single contact grouping

Insert Material Specification:

Mil-m-14 type sdg-f or gdi-30f military specification single material response single mating end

Included Contact Quantity:

56 single mating end single contact grouping

Included Contact Type:

Hermaphrodite single mating end single contact grouping

Special Features:

Polarized in position 1

Precious Material And Location:

Contact surfaces gold

Precious Material And Weight:

0.056 gold grains, troy

Precious Material:

Gold

Test Data Document:

81349-mil-c-28731 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Thread Series Designator:

Unc

Specification Data:

81349-mil-c-28731/13 government specification

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-g-45204 spec.