## NSN 5935-01-167-8158

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-167-8158 **Thread Class:** 2a and 2b **Thread Direction:** Right-hand **Body Style:** Straight shape **Overall Length:** 4.895 inches **Overall Height:** 0.560 inches **Overall Width:** 0.390 inches **Unthreaded Mounting Hole Diameter:** 0.122 inches **Distance Between Mounting Facility Centers:** 4.575 inches **Threaded Device Type:** Coupling facility **Mating End Quantity: Contact Position Arrangement Style:** 2 rows of contacts non-inserted board single mating end **Contact Removability:** Nonremovable single mating end single contact grouping **Contact Maximum Current Rating In Amps:** 5.0 single mating end single contact grouping **Polarization Method:** Jackscrew **Connector Locking Method:** Jackscrew-socket **End Application:** An/ss0-8 (v) Thready Qty Per Inch (tpi): 40 **Thread Size:** 0.112 inches **Terminal Location:** Back single mating end single contact grouping **Contact Material:** Copper alloy single mating end single contact grouping

**Contact Surface Treatment:** 

Tin single mating end single contact grouping

## NSN 5935-01-167-8158

Fiig: A039b0

Electrical Receptacle Connector - Page 2 of 2



Insert Material:
Glass single mating end and plastic single mating end
Terminal Type:
Solder stud single mating end single contact grouping
Contact Material Specification:
Qq-b-626 federal specification single material response single mating end single contact grouping
Included Contact Quantity:
72 single mating end single contact grouping
Thread Series Designator:
Unc
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No