NSN 5935-01-167-8865

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-167-8865 **Body Style:** Straight shape **Overall Length:** 1.541 inches **Overall Height:** 0.679 inches **Overall Width:** 0.494 inches **Unthreaded Mounting Hole Diameter:** 0.120 inches **Distance Between Mounting Facility Centers:** 1.312 inches **Mating End Quantity: Contact Position Arrangement Style:** 7 single mating end **Contact Removability:** Nonremovable single mating end 1st contact grouping **Contact Maximum Current Rating In Amps:** 5.0 single mating end 1st contact grouping **Polarization Method:** Mating end Shell Type: Solid **Connector Locking Method:** Friction **Terminal Location:** Back single mating end 1st contact grouping **Contact Material:** Copper alloy single mating end 1st contact grouping **Contact Surface Treatment:** Gold single mating end 1st contact grouping **Insert Material:** Plastic diallyl phthalate single mating end and glass single mating end **Contact Surface Treatment Specification:** Mil-c-24308 military specification single treatment response single mating end 1st contact grouping **Terminal Type:** Solder well single mating end 1st contact grouping **Shell Material:** Steel

Cadmium

Shell Surface Treatment:

NSN 5935-01-167-8865

Electrical Receptacle Connector - Page 2 of 2



Shell Surface Treatment Specification:

Qq-p-416, type 2, cl 2 federal specification single treatment response

Insert Material Specification:

Mil-m-19833, ty gdi-30f military specification all material responses single mating end

Included Contact Quantity:

5 single mating end 1st contact grouping

Included Contact Type:

Round socket single mating end 1st contact grouping

Precious Material And Location:

Contact surfaces gold

Precious Material And Weight:

0.005 gold grains, troy

Precious Material:

Gold

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-c-24308 spec.