Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-167-8865

Body Style:
Straight shape
Overall Length:
1.541 inches
Overall Height:
0.679 inches
Overall Width:
0.494 inches
Unthreaded Mounting Hole Diameter:
0.120 inches
Distance Between Mounting Facility Centers:
1.312 inches
Mating End Quantity:
1
Contact Position Arrangement Style:
7 single mating end
Contact Removability:
Nonremovable single mating end 1st contact grouping
Contact Maximum Current Rating In Amps:
5.0 single mating end 1st contact grouping
Polarization Method:
Mating end
Shell Type:
Solid
Connector Locking Method:
Friction
Terminal Location:
Back single mating end 1st contact grouping
Contact Material:
Copper alloy single mating end 1st contact grouping
Contact Surface Treatment:
Gold single mating end 1st contact grouping
Insert Material:
Plastic diallyl phthalate single mating end and glass single mating end
Contact Surface Treatment Specification:
Mil-c-24308 military specification single treatment response single mating end 1st contact grouping
Terminal Type:
Solder well single mating end 1st contact grouping
Shell Material:
Steel
Shell Surface Treatment:
Cadmium

Cadmium



end

Shell Surface Treatment Specification:
Qq-p-416, type 2, cl 2 federal specification single treatment response
Insert Material Specification:
Mil-m-19833, ty gdi-30f military specification all material responses single mating
Included Contact Quantity:
5 single mating end 1st contact grouping
Included Contact Type:
Round socket single mating end 1st contact grouping
Precious Material And Location:
Contact surfaces gold
Precious Material And Weight:
0.005 gold grains, troy
Precious Material:
Gold
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A039b0
Mil-std (military Standard):
Mil-c-24308 spec.