

View Online at <https://aerobasegroup.com/nsn/5935-01-167-9049>

**Body Style:**

Right angle type

**Overall Length:**

2.719 inches

**Overall Height:**

0.609 inches

**Overall Width:**

0.719 inches

**Unthreaded Mounting Hole Diameter:**

0.146 inches

**Distance Between Mounting Facility Centers:**

2.375 inches

**Mating End Quantity:**

1

**Contact Position Arrangement Style:**

2 rows of contacts non-inserted board single mating end

**Contact Removability:**

Nonremovable single mating end single contact grouping

**Contact Maximum Current Rating In Amps:**

7.5 single mating end single contact grouping

**Contact Maximum Dc Voltage Rating In Volts:**

725.0 single mating end single contact grouping

**Polarization Method:**

Mating end and shell

**Shell Type:**

Solid

**Connector Locking Method:**

Friction

**Terminal Location:**

Side single mating end single contact grouping

**Contact Material:**

Copper alloy single mating end single contact grouping

**Contact Surface Treatment:**

Gold single mating end single contact grouping

**Insert Material:**

Plastic diallyl phthalate mineral filled single mating end

**Contact Surface Treatment Specification:**

Mil-g-45204 military specification single treatment response single mating end single contact grouping

**Terminal Type:**

Pin single mating end single contact grouping

**Insert Material Specification:**

Mil-m-14 type mdg military specification single material response single mating end

**Shell Guide Type And Location Designator:**

A pin and d pin

**Included Contact Quantity:**

17 single mating end single contact grouping

**Included Contact Type:**

Round pin single mating end single contact grouping

**Precious Material And Location:**

Contact surfaces gold

**Precious Material And Weight:**

0.017 gold grains, troy

**Precious Material:**

Gold

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A039b0

**Mil-std (military Standard):**

Mil-g-45204 spec.