Electrical Plug Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-167-9780

Thread Direction:
Right-hand
Body Style:
Straight shape, internal coupling
Overall Length:
Between 36.5 millimeters and 38.9 millimeters
Overall Diameter:
37.4 millimeters
Environmental Protection:
Moisture proof and salt water resistant and vibration proof
Threaded Device Type:
Back shell
Mating End Quantity:
1
Contact Position Arrangement Style:
17-8 single mating end
Contact Removability:
Removable single mating end single contact grouping
Polarization Method:
Keyway or multiple keyway
Insert Position In Deg:
30.0
Shell Type:
Solid
Connector Locking Method:
Detent
Operating Tempurature Rating:
Operating Tempurature Rating: Between 65.0 degrees celsius and 175.0 degrees celsius
Between 65.0 degrees celsius and 175.0 degrees celsius
Between 65.0 degrees celsius and 175.0 degrees celsius Thread Size:
Between 65.0 degrees celsius and 175.0 degrees celsius Thread Size: 25.0 millimeters
Between 65.0 degrees celsius and 175.0 degrees celsius Thread Size: 25.0 millimeters Thread Pitch In Millimeters: 1.00
Between 65.0 degrees celsius and 175.0 degrees celsius Thread Size: 25.0 millimeters Thread Pitch In Millimeters: 1.00 Terminal Location:
Between 65.0 degrees celsius and 175.0 degrees celsius Thread Size: 25.0 millimeters Thread Pitch In Millimeters: 1.00 Terminal Location: Back single mating end single contact grouping
Between 65.0 degrees celsius and 175.0 degrees celsius Thread Size: 25.0 millimeters Thread Pitch In Millimeters: 1.00 Terminal Location: Back single mating end single contact grouping Contact Material:
Between 65.0 degrees celsius and 175.0 degrees celsius Thread Size: 25.0 millimeters Thread Pitch In Millimeters: 1.00 Terminal Location: Back single mating end single contact grouping Contact Material: Copper alloy single mating end single contact grouping
Between 65.0 degrees celsius and 175.0 degrees celsius Thread Size: 25.0 millimeters Thread Pitch In Millimeters: 1.00 Terminal Location: Back single mating end single contact grouping Contact Material: Copper alloy single mating end single contact grouping Contact Surface Treatment:
Between 65.0 degrees celsius and 175.0 degrees celsius Thread Size: 25.0 millimeters Thread Pitch In Millimeters: 1.00 Terminal Location: Back single mating end single contact grouping Contact Material: Copper alloy single mating end single contact grouping Contact Surface Treatment: Gold single mating end single contact grouping
Between 65.0 degrees celsius and 175.0 degrees celsius Thread Size: 25.0 millimeters Thread Pitch In Millimeters: 1.00 Terminal Location: Back single mating end single contact grouping Contact Material: Copper alloy single mating end single contact grouping Contact Surface Treatment: Gold single mating end single contact grouping Terminal Type:
Between 65.0 degrees celsius and 175.0 degrees celsius Thread Size: 25.0 millimeters Thread Pitch In Millimeters: 1.00 Terminal Location: Back single mating end single contact grouping Contact Material: Copper alloy single mating end single contact grouping Contact Surface Treatment: Gold single mating end single contact grouping Terminal Type: Crimp single mating end single contact grouping
Between 65.0 degrees celsius and 175.0 degrees celsius Thread Size: 25.0 millimeters Thread Pitch In Millimeters: 1.00 Terminal Location: Back single mating end single contact grouping Contact Material: Copper alloy single mating end single contact grouping Contact Surface Treatment: Gold single mating end single contact grouping Terminal Type:

NSN 5935-01-167-9780

Electrical Plug Connector - Page 2 of 2



Shell Surface Treatment:

Cadmium

Shell Surface Treatment Specification:

Qq-p-416 federal specification single treatment response

Thread Tolerance Class:

6g external

Included Contact Quantity:

8 single mating end single contact grouping

Included Contact Type:

Round socket single mating end single contact grouping

Precious Material And Location:

Contact surfaces gold

Precious Material And Weight:

0.008 gold grains, troy

Precious Material:

Gold

Test Data Document:

81349-dod-c-38999 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain

environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Thread Series Designator:

lso m

Specification Data:

81349-dod-c-38999/46 government specification

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A039b0