NSN 5935-01-167-9788

Electrical Plug Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-167-9788

Thread Direction:
Right-hand
Body Style:
Straight shape, internal coupling
Overall Length:
38.9 millimeters
Overall Diameter:
46.5 millimeters
Environmental Protection:
Moisture proof and salt water resistant and vibration proof
Threaded Device Type:
Back shell
Mating End Quantity:
1
Contact Position Arrangement Style:
23-55 single mating end
Contact Removability:
Removable single mating end single contact grouping
Polarization Method:
Keyway or multiple keyway
Insert Position In Deg:
334.0
Shell Type:
Solid
Connector Locking Method:
Detent
Thread Size:
34.0 millimeters
Thread Pitch In Millimeters:
1.00
Terminal Location:
Back single mating end single contact grouping
Contact Material:
Copper alloy single mating end single contact grouping
Contact Surface Treatment:
Gold single mating end single contact grouping
Contact Surface Treatment Specification:
Mil-g-45204 military specification single treatment response single mating end single contact grouping
Terminal Type:
Crimp single mating end single contact grouping
Shell Material:
Aluminum alloy

NSN 5935-01-167-9788Electrical Plug Connector - Page 2 of 2



Shell Surface Treatment: Cadmium Thread Tolerance Class: 6g external Included Contact Quantity:	
Thread Tolerance Class: 6g external	
6g external	
Included Contact Quantity:	
55 single mating end single contact grouping	
Included Contact Type:	
Round socket single mating end single contact grouping	
Precious Material And Location:	
Contact surfaces gold	
Precious Material And Weight:	
0.055 gold grains, troy	
Precious Material:	
Gold	
Test Data Document:	
81349-dod-c-38999 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in the specification type data	ification
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certai	n
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).	
Thread Series Designator:	
lso m	
Specification Data:	
81349-dod-c-38999/46 government specification	
Shelf Life:	
N/a	
Unit Of Measure:	
	
Demilitarization:	
No	
Fiig:	
A039b0	
Mil-std (military Standard):	
Mil-g-45204 spec.	