Electrical Plug Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-167-9789

| Thread Direction:   |
|---|
| Right-hand  |
| Body Style:   |
| Straight shape, internal coupling   |
| Overall Length:   |
| Between 36.5 millimeters and 38.9 millimeters   |
| Overall Diameter:   |
| 34.2 millimeters  |
| Environmental Protection:   |
| Moisture proof and salt water resistant and vibration proof   |
| Threaded Device Type:   |
| Back shell  |
| Mating End Quantity:  |
| 1   |
| Contact Position Arrangement Style:   |
| 15-18 single mating end   |
| Contact Removability:   |
| Removable single mating end single contact grouping   |
| Polarization Method:  |
| Keyway or multiple keyway   |
| Insert Position In Deg:   |
| 34.0  |
| Shell Type:   |
| Solid   |
| Connector Locking Method:   |
| Detent  |
| Operating Tempurature Rating:   |
| Between 65.0 degrees celsius and 175.0 degrees celsius  |
| Thread Size:  |
| 22.0 millimeters  |
| Thread Pitch In Millimeters:  |
| 1.00  |
| Terminal Location:  |
| Back single mating end single contact grouping  |
| Contact Material:   |
| Copper alloy single mating end single contact grouping  |
| Contact Surface Treatment:  |
|   |
| Gold single mating end single contact grouping  |
|   |
| Gold single mating end single contact grouping  |
| Gold single mating end single contact grouping Terminal Type:   |
| Gold single mating end single contact grouping<br>Terminal Type:<br>Crimp single mating end single contact grouping |

## NSN 5935-01-167-9789

Electrical Plug Connector - Page 2 of 2



Shell Surface Treatment:

Cadmium

Shell Surface Treatment Specification:

Qq-p-416 federal specification single treatment response

**Thread Tolerance Class:** 

6g external

Included Contact Quantity:

18 single mating end single contact grouping

Included Contact Type:

Round socket single mating end single contact grouping

Precious Material And Location:

Contact surfaces gold

Precious Material And Weight:

0.018 gold grains, troy

**Precious Material:** 

Gold

## **Test Data Document:**

81349-dod-c-38999 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain

environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

## **Thread Series Designator:**

lso m

Specification Data:

81349-dod-c-38999/46 government specification

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A039b0