Electrical Plug Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-167-9792

Thread Direction:
Right-hand
Body Style:
Straight shape, internal coupling
Overall Length:
Between 36.5 millimeters and 38.9 millimeters
Overall Diameter:
49.7 millimeters
Environmental Protection:
Moisture proof and salt water resistant and vibration proof
Threaded Device Type:
Back shell
Mating End Quantity:
1
Contact Position Arrangement Style:
25-61 single mating end
Contact Removability:
Removable single mating end single contact grouping
Polarization Method:
Keyway or multiple keyway
Insert Position In Deg:
26.0
Shell Type:
Shell Type: Solid
Solid
Solid Connector Locking Method:
Solid Connector Locking Method: Detent
Solid Connector Locking Method: Detent Operating Tempurature Rating:
Solid Connector Locking Method: Detent Operating Tempurature Rating: 65.0 degrees celsius
Solid Connector Locking Method: Detent Operating Tempurature Rating: 65.0 degrees celsius Thread Size:
Solid Connector Locking Method: Detent Operating Tempurature Rating: 65.0 degrees celsius Thread Size: 37.0 millimeters
Solid Connector Locking Method: Detent Operating Tempurature Rating: 65.0 degrees celsius Thread Size: 37.0 millimeters Thread Pitch In Millimeters:
Solid Connector Locking Method: Detent Operating Tempurature Rating: 65.0 degrees celsius Thread Size: 37.0 millimeters Thread Pitch In Millimeters: 1.00
Solid Connector Locking Method: Detent Operating Tempurature Rating: 65.0 degrees celsius Thread Size: 37.0 millimeters Thread Pitch In Millimeters: 1.00 Terminal Location:
Solid Connector Locking Method: Detent Operating Tempurature Rating: 65.0 degrees celsius Thread Size: 37.0 millimeters 37.0 millimeters Ihread Pitch In Millimeters: 1.00 Terminal Location: Back single mating end single contact grouping
Solid Connector Locking Method: Detent Operating Tempurature Rating: 65.0 degrees celsius Thread Size: 37.0 millimeters 37.0 millimeters Thread Pitch In Millimeters: 1.00 Terminal Location: Back single mating end single contact grouping Contact Material:
Solid Connector Locking Method: Detent Operating Tempurature Rating: 65.0 degrees celsius Thread Size: 37.0 millimeters 37.0 millimeters 1.00 Terminal Location: Back single mating end single contact grouping Contact Material:
Solid Connector Locking Method: Detent Operating Tempurature Rating: 65.0 degrees celsius Thread Size: 37.0 millimeters Thread Pitch In Millimeters: 1.00 Terminal Location: Back single mating end single contact grouping Contact Material: Copper alloy single mating end single contact grouping
Solid Connector Locking Method: Detent Operating Tempurature Rating: 65.0 degrees celsius Thread Size: 37.0 millimeters 37.0 millimeters Thread Pitch In Millimeters: 1.00 Terminal Location: Back single mating end single contact grouping Contact Material: Copper alloy single mating end single contact grouping Contact Surface Treatment: Gold single mating end single contact grouping
Solid Connector Locking Method: Detent Operating Tempurature Rating: 65.0 degrees celsius Thread Size: 37.0 millimeters 37.0 millimeters Thread Pitch In Millimeters: 1.00 Terminal Location: Back single mating end single contact grouping Contact Material: Copper alloy single mating end single contact grouping Contact Surface Treatment: Gold single mating end single contact grouping
Solid Connector Locking Method: Detent Operating Tempurature Rating: 65.0 degrees celsius Thread Size: 37.0 millimeters 37.0 millimeters Thread Pitch In Millimeters: 1.00 Terminal Location: Back single mating end single contact grouping Contact Material: Copper alloy single mating end single contact grouping Contact Surface Treatment: Gold single mating end single contact grouping Terminal Type: Crimp single mating end single contact grouping

NSN 5935-01-167-9792

Electrical Plug Connector - Page 2 of 2



Shell Surface Treatment:

Cadmium

Shell Surface Treatment Specification:

Qq-p-416 federal specification single treatment response

Thread Tolerance Class:

6g external

Included Contact Quantity:

61 single mating end single contact grouping

Included Contact Type:

Round socket single mating end single contact grouping

Precious Material And Location:

Contact surfaces gold

Precious Material And Weight:

0.061 gold grains, troy

Precious Material:

Gold

Test Data Document:

81349-dod-c-38999 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain

environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Thread Series Designator:

lso m

Specification Data:

81349-dod-c-38999/46 government specification

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A039b0