Electrical Plug Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-168-0756

#### Body Style:

Straight shape, internal coupling

#### **Overall Length:**

0.875 inches

#### **Overall Diameter:**

0.234 inches

#### **Environmental Protection:**

Corrosion resistant and moisture resistant and shock resistant and vibration resistant

#### Cable Entrance Diameter:

0.110 inches

#### Mating End Quantity:

1

#### **Contact Position Arrangement Style:**

Smb single mating end

#### Contact Removability:

Removable single mating end single contact grouping

#### Contact Maximum Ac Voltage Rating In Volts:

400.0 single mating end single contact grouping

#### Shell Type:

Solid

#### Connector Locking Method:

Friction

#### **Connector Cable Strain Relief Method:**

Compression nut

#### Radio Frequency Type Contact Characteristic Impedance In Ohms:

50.0 single mating end single contact grouping

#### **Terminal Location:**

Back single mating end single contact grouping

#### **Contact Material:**

Copper alloy single mating end single contact grouping

#### **Contact Surface Treatment:**

Gold single mating end single contact grouping

#### **Insert Material:**

Plastic polytetrafluoroethylene single mating end

## Contact Surface Treatment Specification:

Mil-g-45204 military specification single treatment response single mating end single contact grouping

## **Terminal Type:**

Crimp single mating end single contact grouping

### **Contact Material Specification:**

Qq-c-530 federal specification single material response single mating end single contact grouping

## Shell Material:

Copper alloy

# NSN 5935-01-168-0756

Electrical Plug Connector - Page 2 of 2



**Shell Surface Treatment:** Gold Shell Surface Treatment Specification: Mil-g-45204 military specification single treatment response **Shell Material Specification:** Qq-b-626 federal specification single material response **Insert Material Specification:** L-p-403 federal specification single material response single mating end **Included Contact Quantity:** 1 single mating end single contact grouping **Included Contact Type:** Coaxial socket single mating end single contact grouping **Precious Material And Location:** Contact and shell surfaces gold **Precious Material And Weight:** 0.105 gold grains, troy **Precious Material:** Gold Shelf Life: N/a Unit Of Measure: **Demilitarization:** No Fiig: A039b0 Mil-std (military Standard): Mil-g-45204 spec.

---