# NSN 5935-01-168-3028

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-01-168-3028 **Thread Class:** 2b **Thread Direction:** Right-hand **Body Style:** Straight edge type w/mounting flange **Overall Length:** 4.360 inches **Overall Height:** 0.714 inches **Overall Width:** 0.350 inches **Environmental Protection:** Humidity resistant and shock resistant and thermal shock resistant and vibration resistant **Distance Between Mounting Facility Centers:** 4.032 inches **Board Accommodated Length:** 3.584 inches single board **Threaded Device Type:** Coupling facility **Board Accommodated Width:** 0.074 inches **Mating End Quantity: Contact Position Arrangement Style:** Bridged contacts inserted board single mating end **Contact Removability:** Nonremovable single mating end single contact grouping **Contact Maximum Current Rating In Amps:** 5.0 single mating end single contact grouping **Contact Maximum Ac Voltage Rating In Volts:** 600.0 single mating end single contact grouping **Polarization Method:** Mating end **Connector Locking Method:** Friction Thready Qty Per Inch (tpi): 40 **Thread Size:** 0.112 inches

Terminal Location:

Back single mating end single contact grouping

# NSN 5935-01-168-3028

Electrical Receptacle Connector - Page 2 of 2



#### **Contact Material:**

Copper alloy single mating end single contact grouping

#### **Contact Surface Treatment:**

Gold single mating end single contact grouping and copper alloy single mating end single contact grouping

#### **Insert Material:**

Plastic diallyl phthalate single mating end

# **Contact Surface Treatment Specification:**

Mil-c-21097 military specification all treatment responses single mating end single contact grouping

## **Terminal Type:**

Tab, solder lug single mating end single contact grouping

#### **Insert Material Specification:**

Mil-14 ty sdg-f military specification single material response single mating end

#### **Included Contact Quantity:**

40 single mating end single contact grouping

#### **Included Contact Type:**

Leaf spring single mating end single contact grouping

#### **Special Features:**

Furnished items - polarizing key

#### **Precious Material And Location:**

Contact surfaces gold

## **Precious Material And Weight:**

0.040 gold grains, troy

# **Precious Material:**

Gold

# Thread Series Designator:

Unc

#### **Shelf Life:**

N/a

# **Unit Of Measure:**

--

## Demilitarization:

No

# Fiig:

A039b0

# Mil-std (military Standard):

Mil-c-21097 spec.