

View Online at <https://aerobasegroup.com/nsn/5935-01-168-3888>

Body Style:

Straight type

Overall Length:

Between 2.295 inches and 2.305 inches

Overall Height:

0.595 inches

Overall Width:

Between 0.357 inches and 0.367 inches

Environmental Protection:

Humidity resistant and salt water resistant and thermal shock resistant

Unthreaded Mounting Hole Diameter:

Between 0.143 inches and 0.149 inches

Distance Between Mounting Facility Centers:

2.050 inches

Mating End Quantity:

1

Contact Position Arrangement Style:

2 rows of contacts non-inserted board single mating end

Contact Removability:

Nonremovable single mating end single contact grouping

Polarization Method:

Mating end

Connector Locking Method:

Friction

Terminal Location:

Back single mating end single contact grouping

Contact Material:

Copper alloy single mating end single contact grouping

Contact Surface Treatment:

Gold single mating end single contact grouping and nickel single mating end single contact grouping

Insert Material:

Plastic polyester single mating end

Contact Surface Treatment Specification:

Mil-g-45204, type 2, cl 1, grade c military specification 1st treatment response single mating end single contact grouping and qq-n-290, cl 1 federal specification 2nd treatment response single mating end single contact grouping

Terminal Type:

Wire wrap single mating end single contact grouping

Insert Material Specification:

Mil-m-24519 military specification single material response single mating end

Included Contact Quantity:

22 single mating end single contact grouping

Included Contact Type:

Hermaphrodite single mating end single contact grouping

Precious Material And Location:

Contact surfaces gold

Precious Material And Weight:

0.022 gold grains, troy

Precious Material:

Gold

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-g-45204 spec.